

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 13405

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Roaring Springs "B"

9. WELL NO.

Fed.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Unit J

Sec. 14-20S-26E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1.

OIL WELL ☐ GAS WELL ☐ OTHER Dry hole

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

MAY 18 1979

3. ADDRESS OF OPERATOR

207 South Fourth Street - Artesia, NM 88210.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface 1980' FSL &amp; 1980' FEL of Section 14-20S-26E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3313' KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☒  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

☐  
☐  
☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Bone Springs perforations 4808-30' and not commercial. We propose to abandon this zone by cutting and pulling casing from approximately 4400'. Will lay down casing and run tubing 50' inside the 4½" stub, spot 35 sacks cement (100' plug) w/tubing at 2600' and mud in hole, spot 35 sacks (2600-2500'). WOC. Will then drill stem test the 1st Bone Springs. If not commercial, will spot 35 sacks across the casing shoe and set dry hole marker in cement plug at the surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Eddy R. Stall*

TITLE

Engineer

DATE

5-11-79

(This space for Federal or State office use)

APPROVED BY

ALBERT R. STALL

TITLE

DISTRICT ENGINEER

DATE

MAY 17 1979

CONDITIONS OF APPROVAL, IF ANY: