	NMOCC COPY		,
Form 9-331 (May 1963)	WITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	SUBMIT IN A CLICATE• (Other instructions on re- verse side)	Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM 16624 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not 1	SUNDRY NOTICES AND REPORTS ON se this form for proposals to drill or to deepen or plug back i Use "APPLICATION FOR PERMIT-" for such propos	WELLS to a different reservoir. als.)	
1. OIL GAS WEIL OTHER		RECEIVED	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Hanagan Petroleum Corporation		DEC 26 1978	8. FARM OR LEASE NAME Rifle Federal
P.O. Box 1737, Roswell, New Mexico 88201 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 1980' FWL			2 10. FIELD AND FOOL, OR WILDCAT Undesignated Stratican 11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA
14, PERMIT NO.	15. ELEVATIONS (Show whether DF, RT,	GR, etc.)	28-215-26E 12. COUNTY OB PARISH 13. STATE
	3338 GR		Eddy N.M.
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
	NOTICE OF INTENTION TO:	- V	DENT REPORT OF:
TEST WATER FRACTURE TH		WATER SHUT-OFF	ALTERING CASING
SHOOT OR AC		SHOOTING OR ACIDIZING	ABANDONMENT*
CEPAIR WELT (Other)	CHANGE PLANS	(NOTE: Report results Completion or Recomp	of multiple completion on Well etion Report and Log form.)
17. DESCRIBE PRO proposed v nent to this	OSED OR COMPLETED OPERATIONS (Clearly state all pertinent de ork. If well is directionally drilled, give subsurface locations	tails, and give pertinent dates, and measured and true vertic:	including estimated date of starting any al depths for all markers and zones perti-
 12/11/78: Spud 12: Noon Moranco Contractor TD 145', 17½" hole ran 3 jts. 13 3/8" 48# H-40 casing set @ 126' w/100 sx. Class "C" + 2% CaCl. Plug down @ 6:40 P.M. 12/12/78. Cement did not circ. Put 8½ yds Ready Mix circ. 1.32 Slurry Vol. CU. ft. 1 sx. 750 temp, Slurry mixed, est temp @ 750, compressive strength 560#, Drlg. plug 7:00 a.m. 12/ 13/78, WOC 12 hrs. press up w/600# for 30" no press. drop. 12/17/78: TD 2340', 12¼" & 11" hole, Ran 58 jts. 8 5/8" 24# & 32# ST&C (2366', set @ 2340' cemented w/800 sx. Howco lite - ¼# Flocel, 5# gilsonite 2% CaCl + 150 sx. Class "C" + 2% CaCl plug down 9:30 A.M. 12/18/78. Cement circ. est. 170 sx. excess, W.O.C. 23½ hrs., Press up 1800#, no press. drop, drlg. ahead. 			
			RECEIVED
			DEC 21 1978
			U.S. GEULUGICAL SURVEY ARTESIA, NEW MEXICO
-	If y that the foregoing is true and correct	ıt	DATE 12/20/78
(This space	or Foderel or State office use)	NG DISTRICT ENGINEE	R DATE DEC 22 1978
APPROVED CONDITION	BY <u>Your COL XAVEAL</u> TITLE		

*See Instructions on Reverse Side