16.

TED STATES U TED STATES SUBMIT IN TRI OEPARTMENT OF THE INTERIOR (Other Instruction verse side)

GEOLOGICAL SURVEY

'ATE

5. LEASE DESIGNATION AND SERIAL NO.

NM-8665

CLINIDAY NOTICES AND DEPONTS ON	WELLO	6. IF INDIAN, ALLOTTEE OR TRIBE NA
SUNDRY NOTICES AND REPORTS ON	WELLS I	

	(Do not use this form for proposa Use "APPLICA"	ls to drill or to deepen or plug FION FOR PERMIT—" for such 1	back RECEIVED	
1.	· · ·	X-Dry Hole		7. UNIT AGREEMENT NAME
2.	Morris R. Antwei	i1	MAR 1 2 1979	8. FARM OR LEASE NAME M-H Federal Com.
3.	Box 2010, Hobbs			9. WELL NO.
4 .	LOCATION OF WELL (Report location cle See also space 17 below.) At surface	arly and in accordance with any	RECEIVED.	10. FIELD AND POOL, OR WILDCAT ()/ / MCKittrick Hills,
	660' FSL & 1650	' FWL	MAR 21 1979	11. SEC., T., E., M., OR BLE. AND SURVEY OR AREA Sec-1-T22S-R24E
14.	PERMIT NO.	15. ELEVATIONS (Show whether DI 3854 GR	C, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE Eddy N.M.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUEN	SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDON MENT*	
REPAIR WELL	CHANGE PLANS	(Other)		
(Other)	·	(NOTE: Report results of Completion or Recompletion	multiple completion on Well on Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

TD 7952' Propose to P & A as follows:

- (1)Hole loaded W/9.1#/gal - 34 Sec. Viscosity Mud.
- (2) Spot 55 sx. - 150' cement plug 7800'-7950' across Cisco reef.
- (3) Spot 55 sx. - 150' cement plug 6500'-6650'.
- Spot 35 sx. -100' cement plug 4900'-5000'. (4)
- Spot 55 sx. 150' cement plug 3400' 3550' top of (5) Bone Springs.
- Spot 35 sx. 100' cement plug 1575' 1675' across (6) 8-5/8" casing shoe.
- Spot 10 sx. 25" cement plug at surface. **(7)**

Proposed procedure approved orally 8 March, 1979. Jim Knauf - U.S.G.S. - Artesia.

18. I hereby certify that the foregoing is true and correct		
SIGNED RMWilliam	TITLE Agent	DATE 9 March, 197
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE ACTING DISTRICT ENGINEER	DATE MAR 2 0 1979