

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ X- Dry Hole

2. NAME OF OPERATOR
Morris R. Antweil ✓

3. ADDRESS OF OPERATOR
Box 2010, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
660' FSL and 1650' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3854' GR

5. LEASE DESIGNATION AND SERIAL NO.
NM-8665

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
M-H Federal Com.

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
McKittrick Hills Upper Penn.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1 - T22S-R24E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mex.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒ X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and pertinent to this work.)*

TD 7952' Plugged and Abandoned as follows:

- (1) Hole loaded W/9.1#/gal. 34 Sec. Viscosity Mud.
- (2) Spotted 55 sx. - 150' cement plug 7800'-7950' across Cisco reef.
- (3) Spotted 55 sx. - 150' cement plug 6500'-6650'.
- (4) Spotted 35 sx. - 100' cement plug 4900'-5000'.
- (5) Spotted 55 sx. - 150' cement plug 3400'-3550' top of Bone Springs.
- (6) Spotted 35 sx. - 100' cement plug 1575'-1675' across 8-5/8" casing shoe.
- (7) Spotted 10 sx. - 25' cement plug at surface w/marker.

Plug circulated to spot thru drill pipe. Well P & A 9 March 1979.

18. I hereby certify that the foregoing is true and correct

SIGNED R. M. Williams

TITLE Agent

DATE 3/22/79

(This space for Federal or State office use)

APPROVED BY Roger A. Chapman

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:
APR 28 1981

for JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

MAY 5 1981

O. C. D.
ARTESIA, OFFICE

RECEIVED