

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒DEEPEN ☐PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☐GAS
WELL ☒

OTHER

SINGLE
ZONE ☒MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

DAVID FASKEN

3. ADDRESS OF OPERATOR

608 First National Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface

3300' FSL & 1980' FEL

At proposed prod. zone Sec. 5, T-21-S, R-24-E

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE

14 miles Southwest of Lakewood, New Mexico

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drlg. unit line, if any)

1980'

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

1860'

16. NO. OF ACRES IN LEASE

926.46 Comm. Tract

19. PROPOSED DEPTH

9900'

17. NO. OF ACRES ASSIGNED
TO THIS WELL

320

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3748.8' GR

22. APPROX. DATE WORK WILL START*

January 23, 1979

23.

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17-1/2"	13-3/8"	48# H-40	400'	Circ.--est 400 sx
12-1/4"	8-5/8"	24# & 32# K-55	3000'	Circ.--est 1100 sx
7-7/8"	4-1/2"	11.6 J-55 & N-80	9900'	775 sx

- (1) Proposed Drilling Program - See Attachment #1
- (2) The surface formation is the Queen gypsum of Permian Age
- (3) Estimated Tops - Queen ----- 0
3rd Bone Springs -- 6650
Wolfcamp ----- 7100
Cisco ----- 7830
Morrow ----- 9480
- (4) Blow Out Preventer Specifications - See Attachment #2
- (5) No abnormal pressure zones anticipated
- (6) Duration of drilling operations estimated 40 days.
- (7) Acreage dedicated to gas contract.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED Robert H. Angewine TITLE AgentDATE January 15, 1979

(This space for Federal or State office use)

PERMIT NO. _____

APPROVAL DATE 2-13-79

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:



NMOCC COPY

United States Department of the Interior

GEOLOGICAL SURVEY
P. O. Drawer U
Artesia, New Mexico 88210

FEB 13 1979

David Fasken
608 First National Bank Building
Midland, Texas 79701

DAVID FASKEN
Shell Federal Com. No. 4
3300 FSL 1980 FEL Sec. 5, T21S, R24E
Eddy County Lease No. NM-021029

Above Data Required on Well Sign

Gentlemen:

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 9,900 feet to test the Morrow is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

1. Drilling operations authorized are subject to compliance with the attached General Requirements for Oil and Gas Operations on Federal Leases, dated July 1, 1978.
2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the Surface Use Plan and these Conditions of Approval including the attached General Requirements.
3. Submit a Daily Report of Operations from spud date until the well is completed and the Well Completion Report (form 9-330) is filed. The report should be not less than 8" x 5" in size and each page should identify the well.
4. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Guidelines. The color used should simulate sandstone brown (Federal Standard Color No. 595A, color 20318 or 30318).
5. Before drilling below the 8-5/8" casing, the blowout preventer assembly will consist of a minimum of one annular type and two ram type preventers.
6. A kelly cock will be installed and maintained in operable condition.
7. After setting the 8-5/8" casing string and before drilling into the Wolfcamp formation, the blowout preventers and related control equipment shall be pressure tested to rated working pressures by an independent service company. Any equipment failing to test satisfactorily shall be repaired or replaced. This office should be notified in sufficient time for a representative to witness the tests and shall be furnished a copy of the pressure test report.



8. Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be installed and operating before drilling into the Wolfcamp formation and used until production casing is run and cemented. Monitoring equipment shall consist of the following:
- (1) A recording pit level indicator to determine pit volume gains and losses.
 - (2) A mud volume measuring device for accurately determining mud volume necessary to fill the hole on trips.
 - (3) A flow sensor on the flow-line to warn of any abnormal mud returns from the well.
9. Notify the Survey in sufficient time to witness the cementing of the 8-5/8" casing.
10. Cement behind the 13-3/8" and 8-5/8" casing must be circulated.

Sincerely yours,

(Orig. Sgd.) ALBERT R. STALL

Albert R. Stall
Acting District Engineer

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

MEXICO OIL CONSERVATION COMMIS.
WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-102
Supersedes C-128
Effective 1-1-65

All distances must be from the outer boundaries of the Section.

Operator David Fasken			Lease Shell Fed. Com.			Well No. 4		
Plot Letter O	Section 5	Township 21 South		Range 24 East	County Eddy			
Actual Footage Location of Well: 3300 feet from the South line and 1930 feet from the East line								
Ground Level Elev. 3748.8	Producing Formation Morrow		Pool Cemetery Morrow Gas			Dedicated Acreage: 320 Acres		

1. Outline the acreage dedicated to the subject well by colored pencil or hatchure marks on the plat below.
2. If more than one lease is dedicated to the well, on the each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

RECEIVED

JAN 23 1979


U.S. GEOLOGICAL SURVEY

ARTESIA, NEW MEXICO

☒ Yes ☐ No If answer is "no" list the owners and tract descriptions which have actually been consolidated. Communitized - All Of Section #5

If answer is "no" list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.)

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Robert H. Angevine
Name

Robert H. Angevine

Position
Agent

Company
Henry Engineering

Date
January 15, 1979

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed
January 10, 1979

Registered Professional Engineer and/or Land Surveyor

John W. West

Certificate No. **John W. West 676**

Ronald J. Eidson 3239

0 330 660 990 1320 1650 1980 2310 2640 2970 3300

RECOMMENDED DRILLING & COMPLETION PROCEDURE

A.F.E. NO. 424

David Fasken ----- SHELL FEDERAL COMM. NO. 4 ----- Cemetery Morrow Field
Eddy County, New Mexico


1. Drill 17-1/2" hole to 400' with spud mud.
2. Set 13-3/8" casing at 400', cement to surface and install 12" x 3000 PSI W.P. casinghead and B.O.P. stack. (Est. 250 sx Class "C" w/2% CaCl.)
3. Drill 12-1/4" hole with water from 400' to 3000', control seepage with paper. Dry drill if complete loss of returns is experienced.
4. Load hole with 34 sec. viscosity mud at 3000', if hole is showing severe seepage, otherwise run casing with water in hole.
5. Set and cement 8-5/8" casing at 3000' with sufficient cement to circulate. (Estimate 900 sx. Halliburton Lite, 1/2# Flocele, slurry wt. 12.8#/gal. + 200 sx. Incor Neat with 2% CaCl, slurry wt. 14.8#/gal.). W.O.C. 24 hrs. Install 12" - 3000 PSI W.P. X 10" - 3000 PSI W.P. spool with secondary seal and bit guide, choke manifold, B.O.P., and Hydril.
6. Test casing, casing spool, B.O.P., and choke manifold to 3000 psig with Yellow Jacket. Install P.V.T. equipment and flow sensor at nipple up or before 7500' is reached.
7. Drill 7-7/8" hole to a total depth of 9900' using water to drill to 6500', use 4% KCl brine to 9400', mud up with polymer starch mud with 8.7#/gal., 45 sec. viscosity, 10 cc water loss. At 9400' increase viscosity as necessary to maintain hole to total depth.
8. Drill stem test all shows.
9. Run logs (Combination CNL-FDC w/Gamma Ray, DLL, and Dip Meter.)
10. Set and cement 4-1/2" oil string (resin coated and centralized through pay zone) with 775 sx. Class "H" cement with 5.4# KCl and 0.8% Halad-22. Pump plug down with 5% KCl packer fluid. Run temperature survey to locate cement top.
11. Install 10" - 3000 PSI W.P. X 6" - 3000 PSI W.P. tubinghead and Christmas Tree.
12. Move out rotary rig and move in pulling unit.
13. Pressure test casing and head to 3000 psig.
14. Install B.O.P.

- 1 -

JBH:1-9-79

Recommended Drilling and Completion Procedure
A.F.E. No. 424
Shell Federal Comm. No. 4

15. Run tubing, 2-3/8" EUE AB modified, and packer.
16. Swab well down.
17. Control pressure, perforate with "thru-tubing" perforating gun.
18. Production test well.
19. Stimulate well as necessary.
20. Clean up treating fluid.
21. Flow test well.
22. Run C.A.O.F.P. and pressure build up.
23. Connect surface equipment.



MULTIPOINT SURFACE USE AND OPERATIONS PLAN


for

DAVID FASKEN

Shell Federal Comm. No. 4

1980' FEL, 3300' FSL Sec. 5, T-21-S, R-26-E, NMPM

EDDY COUNTY, NEW MEXICO



1. Existing Roads. The attached plat of a portion of the FOSTER RANCH NEW MEXICO quadrangle sheet shows all existing roads in the Cemetery Morrow Field in the area of these proposed wells. Existing lease roads used will be maintained by blading and watering as necessary.
2. Planned Access Roads. The attached plat referenced in Item 1 shows the planned new access road as a single dashed line highlighted in red. The footage of new to Shell Federal Comm. No. 4 is 700 ft. The road bed will follow the surface contour and no cut or fill is anticipated.

The road bed will be 12' in width. Due to the short lengths of new road, no turnouts are planned. No fences will be cut, and no cattleguards are required.
3. Location of Existing Wells. Existing wells are shown on the attached plat.
4. Location of tank batteries, production facilities, etc. The gas line operated by David Fasken connecting the Ross Federal No. 1 to the N.G.P.L. System at Shell Federal No. 1 is shown on the attached plat - highlighted in yellow. All condensate tanks, separating equipment, dehydrators, and gas meters are located on the well pads. It is anticipated that a new gas gathering system will be constructed to the successful wells, however, this cannot be planned until (1) production is established, and (2) negotiations between producer and purchaser are completed.
5. Location and type of water supply, etc. Windmills and springs are shown on the attached plat. The source of drilling water will be from a private well on fee land in the SE - 1/4 of Section 32, T-20-S, R-25-E, NMPM. Temporary lines on the surface will be laid to each proposed well.
6. Source of construction materials. Road surfacing caliche will be supplied from existing pits on Federal Lands in the SW-1/4 of Section 5 and the SW-1/4 of Section 4, T-21-S, R-24-E, NMPM as shown on the attached plat by purple triangles.

7. Methods for handling waste disposal. Cuttings from the well bore will be contained in conventional earth reserve pits. The top soil will be used in the pit walls and used to cover the pits after they have been dried and leveled.

Garbage will be burned in a burner pit dug in the reserve pit excavation in an area cleared of all flammable vegetation and materials.

The only salts and chemicals anticipated to be used will be in the drilling mud and will be buried after the mud in the reserve pit with the cuttings has dried.

Sewage will be disposed of into a temporary septic tank dug at the rig trailer house. This will be filled with dirt, covered with top soil and leveled at the completion of the well.

Drilling fluids will be allowed to dry in the reserve pits and will be buried with the cuttings and backfilled with top soil.

Produced oil and water will be contained in test tanks and the oil trucked to the nearest pipeline and the water hauled by transport truck to the nearest commercial disposal well and injected therein.

8. Ancillary facilities. None are planned.

9. Well site layout. See attached plat.

10. Restoration of the Surface. The location will be reshaped to the original contour of the surface except for the area needed to service the well. Unnecessary pad and roadway will be "ripped" to help with recovery of natural plants.

START: 60 Days after completion of well.

END: 120 Days after completion of well.

11. Other information. All lands are Federal ownership for roads and locations administered by the Bureau of Land Management and utilized for cattle grazing by the Richard Howell, et al Ranch.

The land is a gypsum soil sparsely vegetated with grease wood, grass, spanish dagger and mesquite scrub. The U.S. Soil Conservation Service describes this soil officially as Reeves Gypsum land complex and Gypsum land cottonwood complex with zero to 3° slopes.

There are no geologic or geographic hazards and the land has been checked and found devoid of archeological sites (see special report by New Mexico Archaeology Service, Inc. forwarded to your office.)

12. Operator's representative.


James B. Henry, Agent for David Fasken
Henry Engineering
807 First National Bank Building
Midland, Texas 79701


Business Phone: 1-915-683-1893
Home Phone: 1-915-694-0137

13. Certification.

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operators proposed herein will be performed by David Fasken and his contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved.


January 16, 1979


James B. Henry
Agent for David Fasken



HENRY ENGINEERING
MIDLAND, TEXAS

RIG & WELL SITE PLAT
SHELL FEDERAL COM. V.
No 4



QUADRANGLE LOCATION

BLACKTOP TO
MARATHON I.B.
PLANT

ROAD CLASSIFICATION

Light-duty ————— Unimproved dirt - - - - -

- - - - - Proposed New Road

FOSTER RANCH, N. MEX.
N3230-W10430/7.5

1957

BLACKTOP
TO ARTESIA-CARLSBAD
HWY

WEST CARLSBAD
T. 62500

HENRY ENGINEERING

SUBJECT. BLOWOUT PREVENTER

FILE: _____

STACK

DATE: _____

ENGINEERING MEMORANDUM

