

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

MAR 13 1980

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

ARTESIAN OFFICE

LC-067144
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

BIG EDDY UNIT

8. FARM OR LEASE NAME

BIG EDDY UNIT

9. WELL NO.

74

10. FIELD AND POOL, OR WILDCAT

INDIAN FLATS MALLOW

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 25, 215, 28E

12. COUNTY OR PARISH 13. STATE

EDDY N. Mex.

1. NAME OF OPERATOR

PERRY R. BASS

2. ADDRESS OF OPERATOR

Box 2760, MIDLAND, TX

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface
660' FNL + 1980' FEL OF SECTION - UNIT LETTER B.

4. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GK, etc.)

3218' GL 3236' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACURE TREAT

MULTIPLE COMPLETE

FRACURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) 8 5/8" CASING SETTING

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

DRILLED 11" HOLE TO 2772'. RAN CALIPER SURVEY.

RAN 69 JTS 8 5/8" 28# 5-90 STWC CASING. SET @ 2772' WITH

SHOE, FLOAT COLLAR, 4 CENTRALIZERS AND CEMENT BASSET @ 720'.

CEMENTED WITH 200 SKS "THICKSET" PLUS ADDITIVES AND 800 SKS "LITE"

PLUS ADDITIVES. TAILOR WITH 200 SKS CLASS "C". CIRCULATED OUT 350

SKS. PLUG DOWN @ 8:20 PM FEB. 29, 1980. HAD WATER FLOW BETWEEN

11 3/4" & 8 5/8" CASING. USGS NOTIFIED BUT DID NOT WITNESS - SQUEEZED

WITH 100 SKS CLASS "H" WITH 2% CaCl2. WOC 22 HOURS. TESTED 8 5/8"

TO 2000# - HOLD O.K. DRILLED CEMENT PLUG AND SHOE - TESTED

CASING SEAT TO 600# - HOLD O.K. COMMENCED DRILLING 7 7/8" HOLE.

18. I hereby certify that the foregoing is true and correct

SIGNED H. P. Mundy, Jr.

TITLE Asst. Prod. Clerk

DATE Mar. 11, 1980

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) GEORGE H. STEWART

TITLE Asst. District Engineer

DATE MAR 12 1980

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.