

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TR. CATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 9194

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sacahuiste KE Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREASec. 34-22S-23E  
Unit 0 NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

APR 25 1979

2. NAME OF OPERATOR

Yates Petroleum Corporation

O. C. C.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FSL &amp; 1980' FEL of Section 34-22S-23E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4239' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Production Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 10106' - Ran 252 joints of 5½" 17# N-80 & K-55 LT&C casing as follows  
26 joints 17# N-80 (1066'), 199 joints 17# K-55 (7896'), 27 joints 17#  
N-80 1066') (Total 10028') of casing set at 10018', shoe at 10018',  
float collar at 9977'. Ran 15 centralizers. Cemented as follows:  
With 6 bbls CW 100 wash, weighted to 9.5 ppg w/KCL. 555 sacks 50-50  
Poz, 3/10% D-65, 5#/sack KCL, 3/10% gal/sack D-108, 130 sacks H Self  
Stress, 3/10% gal/sack D-108, 3/10% D-65, 5#/sack KCL, 1/10% D-13.  
PD 4:30 AM 4-15-79. WOC and tested to 2000#. OK. Ran Temperature  
Survey and found top of cement at 6450', WLPBTD 9952'.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Johnson*

TITLE

Geol. Secty

DATE 4-21-79

(This space for Federal or State office use)

APPROVED BY

(Sig. Sgd.) ALBERT R. STALL

TITLE

NOTING DISTRICT ENGINEER

DATE

APR 24 1979

CONDITIONS OF APPROVAL, IF ANY: