

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instruction reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

|   |  |  |  |
|---|--|--|--|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER   |  | 5. LEASE DESIGNATION AND SERIAL NO.<br>NM-0486483                            |  |
| 2. NAME OF OPERATOR<br>Durham, Inc.   |  | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME   |  |
| 3. ADDRESS OF OPERATOR<br>219 S. Colorado, Midland, TX 79701  |  | 7. UNIT AGREEMENT NAME   |  |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*<br>See also space 17 below.)<br>At surface<br>660' FNL x 2010' FEL |  | 8. FARM OR LEASE NAME<br>Shell-Federal Com.                                  |  |
| 14. PERMIT NO.  |  | 9. WELL NO.<br>1   |  |
| 15. ELEVATIONS (Show whether DE, RT, GR, etc.)<br>3865' KB  |  | 10. FIELD AND POOL, OR WILDCAT<br>Cemetery (Morrow)                          |  |
|   |  | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA<br>Sec. 8, T-21-S<br>R-24-E |  |
|   |  | 12. COUNTY OR PARISH<br>Eddy   |  |
|   |  | 13. STATE<br>N.M.  |  |

AUG 1 1979

O.C.C.  
ARTESIA, OFFICE

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

X

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Plug #1 - CIBP to be set at 9500' and capped with 5 sx Class H by dump bailer.
2. Casing will be cut at freepoint (top of cement behind 5½" casing at 7800' by temp. survey) and 5½" casing will be pulled.
3. Plug #2 - 50 sx Class H from 100' below 5½" casing stub to 100' above 5½" casing stub.\*
4. Plug #3 - 50 sx Class H from 6150'-6300'.\*
5. Plug #4 - 50 sx Class H from 4650'-4800'.\*
6. Plug #5 - 75 sx Class H from 3129'-3279' (75' above and below 9 5/8" casing shoe).\*
7. Plug #6 - 10 sx Class H at surface.\*
8. Wellhead will be cut off and ¼" steel plate will be welded on stub with 4' dry hole marker installed per applicable State requirements.

\* Plugs 2 through 6 will be applied through tubing. Hole between cement plugs will be filled with 10.0#/gal brine.  
The above procedure was verbally approved by Mr. Joe Lara, June 6, 1979.

RECEIVED

JUL 11 1979

U.S. GEOLOGICAL SURVEY

ARTESIA, NEW MEXICO

DATE July 7, 1979

18. I hereby certify that the foregoing is true and correct

SIGNED

*Les Skinner*

TITLE

Engineer

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) ALBERT R. STALL

TITLE ACTING DISTRICT ENGINEER

DATE JUL 31 1979

CONDITIONS OF APPROVAL, IF ANY: