

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
reverse side)Form approved,
Budget Bureau No. 42 R1424
LEASE DESIGNATION AND SERIAL NO.

NM 9190 B

G. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

OIL WELL ☐ GAS WELL ☒ OTHER ☐ Dry Hole

2. NAME OF OPERATOR

Inexco Oil Company

3. ADDRESS OF OPERATOR

1100 Milam Bldg., Suite 1900, Houston, Texas 77002

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also Space 17 below.)

At surface

660' FNL & 1980 FWL
Sec 12-T22S-R22E

13. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GL, etc.)

4144.5 GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

L. A. Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Morrow-Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

12-T22S-R22E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) Run Casing ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Ran 13 3/8" 48# H-40 casing, set at 500'. Cemented with 500 sx Class "C"
with 8 yds of Redi-Mix around top. Ran 8 5/8" 24# K-55 ST&C casing, set at 2004'.
Cemented with 300 sxs Halliburton Quik-set, 900 sxs Lite wt with 5# gilsonite & 1/4#
floseal, followed by 200 sxs Class "C", cemented with 450 sxs Class "C" thru 1" pipe
in 5 stages

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Assistant Drilling Administrator

5/7/79

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

MAY 21 1979

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side