

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN
(Other Instru
verse side)LICATE*
is on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0144698

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Superior KJ Fed. Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

East Burton Flat

Wildcat Moiraw

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREASec. 7-20S-29E
Unit D NMPPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

SEP 27 1979

2. NAME OF OPERATOR

Yates Petroleum Corporation

O. C. C.

ARTESIA, OFFICE

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

990' FNL & 990' FWL of Section 7-20S-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3274' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set Prod. Csg.

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 11550'; WLPBTD 11453' - Ran 311 joints of 20# & 17# N-80 5½" casing as follows: 28 joints 20# (923'); 267 joints 17# (10486') and 16 joints 17# (151') (Total 11560') of casing set at 11536'. Diff-shoe at 11536' and Diff-Collar at 11504'. Cemented as follows: 250 gallons mud flush, 300 sacks Class H 4/10% CFR-2, 2/10% Halad-22, 5# KCL, 500 sacks 50-50 Poz mix 4/10% CFR-2, 2/10% Halad-22, 5# KCL displaced w/40 bbls KCL water. PD 12:30 PM 9-11-79. WOC and ran Temperature Survey and found top of cement at 7650', WLPBTD 11453'. Tested to 2300#. OK.

RECEIVED

SEP 24 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct.

SIGNED

Christie Imberson

TITLE

Geol. Secty.

DATE 9-22-79

(This space for Federal or State office use)

(Orig. Sgd.) GEORGE H. STEWART

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

ACTING DISTRICT ENGINEER

TITLE

SEP 25 1979

DATE