

UNITED STATES N.M.O.C.D. COPY
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 144698

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

MAY 28 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street, Artesia, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

990 FNL 990 FWL, Section 7-20S-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3288 KB

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Superior KJ Federal Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

E. Burton Flats Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

D - 7 - 20S - 29E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Plugback Same Zone

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/5/80. Loaded hole, pulled tubing, set E-Z drill retainer @ 11400 and cement squeezed Morrow perfs. 11412-416 w/100 sx Class H cement to 1600#. WOC, POOH.

4/15/80. Perf. 11375-377½' w/10 0.50" holes, swab dry, treated w/1000g. 7½% MSA and nitrogen, swab salt water w/gas TSTM, squeezed perfs. 11375-377½ w/75 sx Class H cement to 3500#, retainer @ 11363'. WOC. POOH.

4/22/80. Perf. 11265-281' w/56 0.50" holes, swab dry, treated w/1000g. 7½% MSA and nitrogen, swabbed back load & well flowed 100# on 1/8" ck. Ran BHP.

5/20/80. Load hole, pull tubing and packer, perf. Morrow @ 11188-193 w/20 0.50" holes tubing conveyed gun, GTS but TSTM. Treated perfs. 11188-193 w/1000g. 7½% MSA & N₂, cleaned up and flowed 25# on 1/2" ck. Frac'd w/5000# 100 mesh and 20000# 20/40 sd in 10000g. 5% MS fluid and 5000g. CO₂. Well cleaned up and flowed 130# on 1/2" ck from perfs. 11188-193 and 11265-281' KB. SI for BHP

RECEIVED

MAY 29 1980

O. C. D.

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

Eddie H. Haskins

TITLE

Engineer

DATE

5/27/80

(This space for Federal or State office use)

(Orig. Sgd.) GEORGE H. STEWART

APPROVED BY

TITLE

ENGINEER

DATE

MAY 28 1980

CONDITIONS OF APPROVAL, IF ANY: