

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1980' FNL & 1980' FWL, Sec. 17
AT SURFACE: (Unit E, SW/4 NW/4)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud ☐

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐

☐

☐

☐

RECEIVED

JUN 12 1979

U.S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 5-31-79 MGF Drilling Co. (Rig #23) spudded a 17-1/2" hole at 7:30 a.m.

Drilled to a TD of 396' and set 13-3/8" 54.5# K-55 ST&C casing at 396'.

Cemented with 200 sacks Thix Set and 500 sacks Class C with 2% CACL. Plugged down 3:10 p.m. 6-3-79. Circulated 260 sacks cement. WOC 18 hrs. Tested casing with 800# for 30 min. OK. Reduced hole to 12-1/4" and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Cox

TITLE Admin. Supervisor

DATE 6-7-79

(This space for Federal or State office use)

APPROVED BY (Orig. & 1) ALBERT R. STALLS ACTING DISTRICT ENGINEER

CONDITIONS OF APPROVAL, IF ANY:

0+4 - USGS,A; 1 - Hou; 1 - Susp; 1 - BD; 1 - Read & Stevens