DEPARTNNT OF THE		5. LEASE DESIGNATION AND SEBIAL NO. NM-34650
GEOLOGICAL S		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND RE (Do not use this form for proposals to drill or to dee Use "APPLICATION FOR PERMIT-	PORTS ON WELLS, VE D epen or plug back to a different reservoir. D -" for such proposals.)	· · ·
1. OIL GAS X OTHER	OCT 30 1979	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	O. C. C.	8. FARM OR LEASE NAME
MORRIS R. ANTWEIL	ARTESIA, OFFICE	Indian Wells 9. wELL NO.
Box 2010, Hobbs, New Mexico 88	240	1
<ul> <li>LOCATION OF WELL (Report location clearly and in accorda See also space 17 below.) At surface</li> </ul>	ince with any State requirements.*	10. FIELD AND POOL, OB WILDCAT Wildcat 7
2080' FSL & 1980' FEL Sec. 19-	T22S-R25E	SURVEY OR ABEA Sec.19-T22S-R25E
14. PERMIT NO. 15. ELEVATIONS (S)	how whether DF, RT, GR, etc.)	12. COUNTY OF PARISH 13. STATE Eddy New Mey
16. Check Appropriate Box To	o Indicate Nature of Notice, Report, or (	
NOTICE OF INTENTION TO:	SUBSEC	QUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASIN FRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE ABANDON*	FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) Setting	REPAIRING WELL
REPAIR WELL CHANGE PLANS	(Nome : Papart result	s of multiple completion on Well pletion Report and Log form.)
proposed work. If well is directionally drilled, give so nent to this work.)*	te all pertinent details, and give pertinent date ubsurface locations and measured and true verth	cal depths for all markers and zones per
proposed work. If well is directionally drined, give a	55'. Ran 3082' 4-1/2" T liner hanger @ 7771'. ining 3/4% CFR-2 & 5#/s Reversed out 135 sx. co wing top of cement @ 78	ll.6# N-80 liner Cemented liner x. KCL. Plug ement. After 10'. Released
Drilled 6-1/8" hole to TD 10,8 Set liner 7771' - 10,853' w/BO w/475 sx. Class H cement conta down @ 9:15 PM 19 Oct., 1979. 8 hrs. WOC ran temp survey sho rig. Moving out rig. Will pr	55'. Ran 3082' 4-1/2" T liner hanger @ 7771'. Mining 3/4% CFR-2 & 5#/s Reversed out 135 sx. co owing top of cement @ 78 ressure test liner prior	ll.6# N-80 liner Cemented liner x. KCL. Plug ement. After 10'. Released
Drilled 6-1/8" hole to TD 10,8 Set liner 7771' - 10,853' w/BO w/475 sx. Class H cement conta down @ 9:15 PM 19 Oct., 1979. 8 hrs. WOC ran temp survey sho rig. Moving out rig. Will pr	55'. Ran 3082' 4-1/2" T liner hanger @ 7771'. ining 3/4% CFR-2 & 5#/s Reversed out 135 sx. co owing top of cement @ 78 ressure test liner prior	ll.6# N-80 liner Cemented liner x. KCL. Plug ement. After 10'. Released
proposed work. If well is directionally drined, give a nent to this work.)* Drilled 6-1/8" hole to TD 10,8 Set liner 7771' - 10,853' w/BO w/475 sx. Class H cement conta down @ 9:15 PM 19 Oct., 1979. 8 hrs. WOC ran temp survey sho rig. Moving out rig. Will pr w/well completion. 18. I hereby certify that the foregoing is true and correct	E55'. Ran 3082' 4-1/2" T liner hanger @ 7771'. Aining 3/4% CFR-2 & 5#/sz Reversed out 135 sx. co owing top of cement @ 78 Sessure test liner prior RECEIVED OCT 2 5 1979 U.S. GEULUGICAL SURVEY	<pre>11.6# N-80 liner Cemented liner x. KCL. Plug ement. After 10'. Released to proceeding</pre>
proposed work. If well is directionally drined, give a nent to this work.)* Drilled 6-1/8" hole to TD 10,8 Set liner 7771' - 10,853' w/BO w/475 sx. Class H cement conta down @ 9:15 PM 19 Oct., 1979. 8 hrs. WOC ran temp survey sho rig. Moving out rig. Will pr w/well completion. 18. I hereby certify that the foregoing is true and correct SIGNED	ESSUME MALANS AN ANALY AND	<pre>11.6# N-80 liner Cemented liner x. KCL. Plug ement. After 10'. Released to proceeding</pre>
proposed work. If well is directionally drined, give a nent to this work.)* Drilled 6-1/8" hole to TD 10,8 Set liner 7771' - 10,853' w/BO w/475 sx. Class H cement conta down @ 9:15 PM 19 Oct., 1979. 8 hrs. WOC ran temp survey sho rig. Moving out rig. Will pr w/well completion.	ESSUME MALANS AN ANALY AND	<pre>11.6# N-80 liner Cemented liner x. KCL. Plug ement. After 10'. Released to proceeding</pre>