

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instruction
verse side)

ATE
re-

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM-34560
2. NAME OF OPERATOR MORRIS R. ANTWEIL		6. IF INDIAN, ALLOTTEE OR TRIBE NAME --
3. ADDRESS OF OPERATOR Box 2010, Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME --
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2080' FSL & 1980' FEL Sec. 19-T22S-R25E		8. FARM OR LEASE NAME INDIAN WELLS
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3736' GR		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 19-T22S-R25E
		12. COUNTY OR PARISH Eddy
		13. STATE New Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input checked="" type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <input type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 10,855' PBTD 10,286' Perforated 9376' - 9381', 9456' - 9464', & 9630' - 9636' (Atoka). Ran tubing and set packer @ 9325'. Treated perfs with 2500 gals acid using nitrogen and ball sealers. Rate 3 b/m @ 5200 psi. ISIP 3600 psi. Swabbed 1-1/2 bbls formation water per hour with 70 MCFPD of gas. SITP 1100 psi. Temporarily abandoned completion attempts.

FEB 04 1981

APPROVED

18. I hereby certify that the foregoing is true and correct

SIGNED: *Pm Wilkins*

TITLE: Agent

DATE: 3 February, 1981

(This space for Federal or State office use)

APPROVED BY: PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FEB 5 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side