Form 9-331 Dec. 1973 UNITED STATES	Drawer DD Artesia, NM 882	10 5. LEASE	Form Approved. Budget Bureau No. 42	2-R1424
DEPARTMENT OF THE INTERIOR		NM 055477	/1	
GEOLOGICAL SURVEY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPOR	TS ON WELLS	7. UNIT AGREE	MENT NAME	
(Do not use this form for proposals to drill or to deepen reservoir. Use Form 9-331-C for such proposals.)		8. FARM OR LE		
1. oil gas	RECEIVED BY	TOG Feder	<u>^al</u>	<del></del>
2. NAME OF OPERATOR	JUN 26 1986	9. WELL NO. 1		
J. C. Williamson		10. FIELD OR WILDCAT NAME		
2 ADORESS OF OPERATOR	O. C. D.	East Bur	ton Delaware	
P. O. Box 16 Midland, Texas	7 CARTESIA, OFFICE	11. SEC., T., R.,	M., OR BLK. AND SUR	VEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17		I	ection 16, D-S, R-29-E	
below.) AT SURFACE: 1980' FNL & 2310' FWL		12. COUNTY OR PARISH 13. STATE		
	NL & 2310' FWL	Eddy	New Mexi	со
AT TOTAL DEPTH: 1980' FNL & 2310' FWL		14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		-		
REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, KDB, AND WD)		
		3272.5 GR		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF				
SHOOT OR ACIDIZE	П			
REPAIR WELL			esults of multiple completion	on or zone
PULL OR ALTER CASING		change o	on Form 9–330.)	:
			÷	14 J
ABANDON* L L (other) Plug & Abandon X				
			······································	·
17. DESCRIBE PROPOSED OR COMPLETED Of including estimated date of starting any pr measured and true vertical depths for all m	ronosed work. If well is	ent to this work.)*	tails, and give pertine , give subsurface locat	

Hole filled with mud to 3400'. Bridge plug was set @ 3450' on 8/24/82 with 35' cement plug on top of plug. Mix mud to fill up hole to 1550'. Set 100' plug @ 1550' and a 100' plug @ 682' - 582'. All plugs set inside of 4 1/2" casing on 8/25/82. A 50' plug was set in surface on 8/25/82. A dry hole marker was erected after plate was welded on surface pipe. Well was cleared of debris. The old reserve pit and working have been broken out and leveled and the well site is ready for final inspection.  $\begin{aligned} & \rho_{ost} \neq D-2 \\ & 4-1-8.3 \end{aligned}$ 

Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct SIGNED	9/22/82
Orig: Sgd. Cliq.les C. Dahlon (This space for Federal or State office use)   APPROVED BY Arca Manager   TITLE DATE   CONDITIONS OF APPROVAL, IF ANY: E <sup>r</sup>	SEP 2 7 1982
*See Instructions on Reverse Side	OUL & GAS

E TO MAN MEXICO

PYA

CIST

t