

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Maralo Inc.</u>		Lease <u>N.W. Indian Basin Comm.</u>		Well # <u>1</u>	
Location of Well	Unit <u>2130 S 2430 W</u>	Section <u>2</u>	Township <u>21</u>	Range <u>22</u>	County <u>Eddy</u>
Drilling Contractor	<u>Hondo</u>		Type of Equipment <u>Rotary to start approx. 9-15-79</u>		

** witness* APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 7/8"</u>	<u>48</u>		<u>555</u>	<u>500 cu</u>
<u>11</u>	<u>8 7/8"</u>	<u>24</u>		<u>1400</u>	<u>2500 "</u>
<u>7 1/8</u>	<u>5 1/2"</u>	<u>17+15.5</u>		<u>9400</u>	<u>400</u>

Casing Data:

Surface joints of 8 7/8 inch 24 # Grade K-55
(Approved) (Rejected)

Inspected by M.S. date 9/24/79

Cementing Program

Size of hole 12 1/4 Size of Casing 8 7/8 Sacks cement required

Type of Shoe used port Float collar used no Btm 2 jts welded yes

TD of hole 1400 Set 1400 Feet of 8 7/8 Inch 24 # Grade K-55

New-used csg. @ 1400 with 200 2% sacks neat cement around shoe
+ 200 sax Trix set additives 5# gilsonite - 1/4# fluoride, 2% occ

Plug down @ 4:15 (AM) (PM) Date 9/26/79

Cement circulated yes No. of Sacks 150

Cemented by Halliburton Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: +600 Hall. Lite (10# gilsonite, 1/4# fluoride, 2% occ)

centralizers @ 1360 - 1320 - 1280 - 1240' lost air @ 620'

Barbets @ 605' - 1000' lost ddy break @ 639'