

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424
5. LEASE DESIGNATION AND SERIAL NO.

NM 38458

6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 8

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Burton Flat Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8, T21S, R27E

12. CO. CITY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to design or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR
H. L. Brown, Jr.

3. ADDRESS OF OPERATOR
P. O. Box 2237, Midland, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
ALLOCATION
1980' FNL and 660' FWL of Section 8

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GK, etc.)
3220.6' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☒
(Other) Spud in Progress

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give surface locations and measured and true vertical depths for all markers and zones pertinent to this work.*

Rigged up Parker #34 & spudded 17-1/2" hole @ 10 pm, 12-29-79. Lost circ @ 230', dry drilled to 600'. Finished 17-1/2" hole @ 12:30 pm, 12-31-79. 1-1-80: Ran 15 jts. 12-3/3" 34# csg., set @ 600'. Rigged up BJ, cemented 12-3/4" csg. w/200 sx Surefill and 465 sx Class C w/2% CaCl2. WOC 8 hrs. Recement w/125 sx Class C w/3% CaCl2, WOC 3 hrs. Recement w/125 sx Class C w/3% CaCl2, WOC 3 hrs. Did not circ. all three times. 1-2-80: Recement w/50 sx & 150 sx, circ cmt to surface. Cut off 12-3/4" csg. and weld on head. Nipple up BOP's. Pressure test 12-3/4" csg. w/500 psi for 15", held OK.

RECEIVED

JAN 9 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Jill W. White

TITLE: Production Assistant

DATE 1-7-80

(This space for Federal or State office use)

APPROVED BY

*(sgd.) GEORGE L. S.*TITLE: *Geological Engineer*

DATE

JAN 9 9 1980

CONDITIONS OF APPROVAL, IF ANY: