

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

RECEIVED

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LG-4548
7. Unit Agreement Name
ARTESIA, OFFICE
8. Farm or Lease Name
State
9. Well No.
1
10. Field and Pool, or Wildcat
Morrow
12. County
Eddy

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Pogo Producing Company
3. Address of Operator
Box 10340 Midland, Texas 79702
4. Location of Well
UNIT LETTER M 3300 FEET FROM THE South LINE AND 660 FEET FROM
West LINE, SECTION 2 TOWNSHIP 21S RANGE 28E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3318.8' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>
OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>
OTHER <input type="checkbox"/>
SUBSEQUENT REPORT OF:
REMEDIAL WORK <input type="checkbox"/>
COMMENCE DRILLING OPS. <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>
ALTERING CASING <input type="checkbox"/>
PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

01-21-80: Spudded well @ 6:00 P.M. MST on 1-20-80.

01-22-80: TD 520' Red beds. Ran 12 jts. 13 3/8" 54.5# K-55 Rng 3 ST&C, 516' w/shoe @ 513', baffle @ 474', bottom 2 jts. thread-locked, centralizer on bottom jt. Rig Howco cement w/525 sxs Class "C" w/2% CaCl₂, 14.8 to 15 ppg, good returns throughout job, circ. 84 sxs, bump plug w/150#, held OK. Plug down 1 P.M. 1-21-80. Cut off csg., weld on head, NU.

01-23-80: Test blind rams & casing w/1000# - OK. LD 2-9 1/2" DC. Test Hydril & pipe rams w/1000# - OK. Drill plug & baffle @ 474'; clean out cement.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Div. Operations Manager DATE 1/24/80

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: