

N.M.O.C.D. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TP (Other Instruc
verse side) ICATE* on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-26683

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Antongiovanni MU Fed.

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

Undes. Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASection 1-20S-28E
Unit O NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back or otherwise alter a well.
Use "APPLICATION FOR PERMIT" for such proposals.1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 1980' FEL of Section 1-20S-28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3282' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Set Production Casing ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

TD 11663' - Ran 277 joints of 5½" 20# & 17# N-80 LT&C casing as follows:
22 joints 20# (893'); 240 joints of 17# (10093') and 15 joints 20# (612')
(Total 11598') of casing set at 11552'. DV tool at 10869'. 10 centralizers.
Cemented in 2 stages. 1st stage: 250 gallons mud flush, 190 sacks Class
H, 2/10% Halad 22, 6/10% CFR2, 5#/sack KCL. PD 7:00 PM 4-13-80. 2nd
stage: 250 gallons mud flush, 250 sacks 50-50 Poz, 2/10% Halad 22,
6/10% CFR2, 5#/sack KCL, 625 sacks Class H, 2/10% Halad 22, 6/10% CFR2,
5#/sack KCL. PD 1:30 AM 4-14-80. Displaced both stages with mud.
Top of cement at 6960'.

RECEIVED

MAY 16 1980

O. C. D.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

Christie J. Stewart

TITLE

Geol. Secty.

DATE

5-13-80

(This space for Federal or State office use)

(Orig. Sgd.) GEORGE H. STEWART

DISTRICT ENGINEER

APPROVED BY

TITLE

DATE

MAY 15 1980

CONDITIONS OF APPROVAL, IF ANY: