

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

RECEIVED

APR 25 1980

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-4678	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- ARTESIA OFFICE		7. Unit Agreement Name
2. Name of Operator Amoco Production Company		8. Farm or Lease Name State IE Com
3. Address of Operator P. O. Box 68 Hobbs, NM 88240		9. Well No. <del>Und. Morrow</del> 1
4. Location of Well UNIT LETTER L 2170 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 22-S RANGE 26-E N.M.P.M.		10. Field and Pool, or Wildcat Ind. Snare
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 2900' and ran 9-5/8" 36# K-55 ST&C casing set at 2900'. Cemented with 3100 SX Howco Lite cement and 400 SX Thix set cement and 200 SX Class C cement. Plugged down 7:15 p.m. 4-6-80. Top of cement found by temp survey at approx. 745'. Cemented to surface with 385 SX Class C cement. 435 SX Class C cement. WOC 42-1/2 hours. Tested casing with 1000# for 30 min. Test OK. Reduced hole to 8-3/4" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Admin. Analyst DATE 4-23-80

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE APR 29 1980

CONDITIONS OF APPROVAL, IF ANY:

0+4-NMOCD, A 1-Hou  
1-Burlington Northern

1-Susp 1-BD  
1-Read & Stevens

1-Holly Energy