

RECEIVED

N.M.O.C.D. COPY

C:SF

Form 9-331  
(May 1963)

APR 14 1980

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 28714 NM-0557562  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Citgo Federal Comm

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT  
Undesignated (Morrow)11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 5, T-20-S, R-28-E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

O.C.D. SUNDRY NOTICES AND REPORTS ON WELLS  
ARTESIA, NEW MEXICO  
Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

1100 Wall Towers West, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface2130  
660' FNL, 1980 FEL, Sec. 5, T-20-S, R-28-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,328.6'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

Set 8 5/8" Intermediate Csg

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/4/80 Condition hole for logs. Ran FG Log, Sidewall Neutron Log. Ran 64 jts 8 5/8" 24# K-55 ST&amp;C csg. Set @ 2600'. Cmt w/950 sxs lite-weight cmt w/6# salt, 5# gilsonite, 1/4# flocele per sx plus 200 sxs C1 C w/2% C.C., 5# gilsonite, 1/2# flocele per sx. Cmt circ. 90 sxs. PD @ 3:00 a.m. WOC 18 hrs. Nipple up BOP. Pressure test 8 5/8" csg &amp; BOP to 1000# for 30 minutes Held Okay. Drill ahead w/7 7/8" hole.

RECEIVED

APR 11 1980

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Donald R. Craig

TITLE District Production Engineer DATE 4/9/80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side