

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Drill Bit Bureau No. 1004-1
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Quinoco Petroleum, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 378111, Denver, CO 80237

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FSL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3432.7' GR

ARIES

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Quinoco Petroleum, Inc. plugged-back the Catclaw Draw Unit #15 from the Lower Morrow @10,706 - 10,714' to the Upper Morrow @ 10,544 - 10,608' as follows:

5/16/90 - 5/18/90

1. MIRU completion unit. ND WH.

2. Release Guiberson UNI VI pkr. NU BOP's.

3. RU WL & set 5-1/2" CIBP @ 10,691', cap w/35' of cmt. PBTD @ 10,656'.

4. TIH w/2-3/8" tbg, circ hole w/310 bbls 2% KCl w/pkr fluid. Test CIBP to 500 psi for 15 mins. POOH w/tbg.

5/21/90 - 6/4/90

5. RIH w/4" tbg conveyed guns & seating nipple. Fill tbg w/1000' of 2% KCl, test tbg to 8000 psi. Test tree to 5000 psi. Space out tbg string & set pkr @ 10,344'.

6/5/90

6. ND BOP's. NU WH. Test pkr to 500 psi for 15 mins.

7. Perforate 10,600-10,608', 10,550-10,556', & 10,544-10,547' w/2 JSPF (34 shots total).

8. Place well on production.

ACCEPTED FOR RECORD

AK

JUN 11 1990

18. I hereby certify that the foregoing is true and correct

CARLSBAD, NEW MEXICO

SIGNED Nally S. Richardson TITLE Sr. Ops. Eng. Tech.

DATE 6/18/90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.