

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 911

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling well SEP 15 1980

2. NAME OF OPERATOR DAVID FASKEN ✓ O. C. D.

3. ADDRESS OF OPERATOR ARTESIA, OFFICE
608 First National Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
2684' FNL & 660' FWL

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3195' Gr

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Federal

9. WELL NO.

5

10. FIELD AND POOL OR WILDCAT

Avalon (Morrow)

11. SEC., T., R., M., OR BLE. AND
SURVEY OR AREA

Sec. 1, T-21-S, R-26-E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Cement intermediate casing ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-19 to

8-21-80 - Drilled 12¼" hole to 3000' w/no mud returns since 1698'. Ran in hole w/one type "M" guide shoe (0.72'), one jt 8-5/8" 32#/ft K-55 LT&C csg (39.67'), one float collar (1.63'), 12 jts 8-5/8" 32#/ft K-55 LT&C csg (472.55'), 55 jts 8-5/8" 24#/ft J-55 ST&C csg (2493.50') = total 3008.07', set @ 3004.00'. Cement basket @ 1625'. Cemented w/1000 sx Halliburton-Lite w/½# flocele & 2% CaCl/sk, slurry wt. 12.7#/gal (yield: 1.84 ft³/sk) + 300 sx Thixset w/¼# flocele & 2% CaCl/sk, slurry wt. 14.1#/gal (yield: 1.50 ft³/sk) + 200 sx Class "C" w/2% CaCl/sk, slurry wt. 14.8#/gal (yield: 1.32 ft³/sk). No returns during cementing, plug down @ 6:00 a.m. C.D.T. 8-19-80. WOC 8 hrs & ran temperature survey. Top of cement inside 8-5/8" x 12-1/4" annulus @ 1375'. Stage cemented 8-5/8" x 12-1/4" annulus through 1" pipe w/518 sx Class "C" cement in 8 stages & 1 cu. yd. pea gravel. Circulated 34 sx cement on last stage. Set slips, cut off casing, nipped up BOP's & WOC 22½ hrs. Tested casing @ 1700# for ½ hr - held OK.

RECEIVED

8-22-80 - Drilling 7-7/8" hole @ 3390' with fresh water.

SEP 5 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Jimmy W. Davis, Jr.

TITLE Agent

DATE 9-2-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

P. Chester

SEP 9 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

*See Instructions on Reverse Side