

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN ☐ POLICATE\*  
(Other instr. is on re-  
verse side)Form approved.  
Budget Bureau No. 42-P1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0384625

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Indian Basin

8. FARM OR LEASE NAME

Federal IBD Gas Com

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Indian Basin Upper Penn

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 30, T-21S, R-23E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

## SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL  
WELL ☐ GAS  
WELL ☒ OTHER

2. NAME OF OPERATOR

Marathon Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 2409 Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface800' FNL & 200' FEL  
Sec. 30, T-21S, R-23E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 4069', RKB 4085'

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Production Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*07-26-80 Finished 7 7/8" hole at 6:00 a.m. TD 7500'.  
Ran GR/CNL/FDC/Caliper Loggers TD 7493'.07-27-80 Circulated and conditioned hole. Ran 177 jts 5 1/2" N-80 LT&C, set  
from 17.00' to 7500', depth includes HOWCO float collar and guide shoe.07-28-80 Cemented 5 1/2" casing with 500 gal. mud flush, 310 sx Halliburton lite  
w/1/2% CFR-2 followed by 540 sx Class "H" w/1/2% CFR-2 + 5# KCl. Displaced  
w/126 bbl. mud. Bumped plug w/2200 psi at 7:15 a.m. MST 7-28-80. Floats  
held okay. Set slips w/75,000#.WOC. Nippled down BOP, cut off 5 1/2 csg,  
set seals and nippled up tubinghead, test to 2000# - held okay. Nippled  
up X-mas tree. Rig released at 9:00 p.m. 7-28-80.

18. I hereby certify that the foregoing is true and correct

SIGNED Ralph M DePauwTITLE Production EngineerDATE 7-31-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

AUG 4 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO