

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 06789

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

PERRY R. BASS

3. ADDRESS OF OPERATOR

Box 2760, MIDLAND, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2310' FSL + 1980' FEL OF SECTION - UNIT LETTER J.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3433.7' GL 3451.7' ICB

7. UNIT AGREEMENT NAME

EDDY UNIT

8. FIELD OR LEASE NAME

EDDY UNIT

9. WELL NO.

78

10. FIELD AND POOL, OR WILDCAT

Und. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 35, T. 20 S, R. 30 E

12. COUNTY OR PARISH

EDDY

13. STATE

N. MEX

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) SPUD DATE & SURFACE CSG

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

SPUDDED 15" HOLE @ 8:00 AM, DECEMBER 5, 1980.

DRILLED 15" HOLE TO 397'. RAN 10 JTS 11 3/4" 42# H-40 STVC. SET @ 396.74'. CEM W/500 SKS CLASS "C" PLUS ADDITIVES. PLUG DOWN @ 8:00 PM MST 12-5-80. CIRC. OUT 90 SKS. WOC 23 HRS - TESTED BOPE TO 1000# - HELD OK. COMMENCED DRILL 11" HOLE.

DRILLED 11" HOLE TO 4079'. RAN 30 JTS 8 5/8" S-80 32# STVC AND 63 JTS 8 5/8" K-55 28# STVC. FLOAT COLLAR @ 4028'. EXTERNAL CASING PACKER @ 1678'. DV TOOL @ 1676'. FIRST STAGE CEMENT: 850 SKS "LITE" PLUS ADDITIVES - TAILED W/300 SKS CLASS "C" PLUS ADDITIVES. PLUG DOWN @ 11:46 AM, DECEMBER 17, 1981. SECOND STAGE CEMENT: 900 SKS "LITE" PLUS ADDITIVES - TAILED W/200 SKS CLASS "C" PLUS ADDITIVES. PLUG DOWN @ 6:30 PM DECEMBER 17, 1981. NO RETURNS. PUMPED 100 SKS CLASS "C" DOWN 8 5/8" - 11" ANNULUS - NO RETURNS. PUMPED 200 SKS THIXOTROPIC DOWN ANNULUS FOLLOWED BY 600 SKS "LITE" - NO RETURNS. POURED 1 1/2 YD PEA GRAVEL DOWN BACKSIDE - RAN 1" TO 100' - SOLID @ 100' - PUMPED 25 SKS CLASS "C" - CIRC CEM TO SURFACE. JOB COMPLETED @ 5:00 AM, DECEMBER 19, 1980. WOC 12 HRS. DRILL DU TOOL - TESTED BOPE + CST TO 1000# - HELD OK. COMMENCED DRILL 7 7/8" HOLE.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. P. Hunter, Jr.

TITLE

Asst. Prod. Clerk

DATE

Mar. 17, 1981

(This space for Federal)

ACCEPTED FOR RECORD
PETER W. CHESTER

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

MAR 19 1981

U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO

Instructions on Reverse Side

RECEIVED

MAR 18 1931

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO