

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L);
PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)	OD	DRIIFT ID	WT PER FT	GRADE	THREAD	ANT	WT. IN AIR, WT. IN MUD		REMARKS
							1000 LBS	1000 LBS	
S) 0'-300'	13-3/8"	12.559	48#	H-40	STC	300'	14.4		
I) 0'-2800'	9-5/8"	8.765"	36#	J-55	STC	2800'	100.8		
P) 0'-6900'	5-1/2"	4.767"	17#	K-55	BTRC	6900'	179		
6900'-10,500'	5-1/2"	4.767"	17#	L-80	LT	3600'	61		Sandblast bottom 600' of 5-1/2" csg.

TYPE OF STRING	CENTRALIZERS		SCRATCHER NO. INTERVAL	OTHER ACCESSORY EQUIPMENT (SUCH AS DEGASSERS, MUD. CENTRIFUGE FLOAT COLLARS, ETC. - SPECIFY)		REMARKS
	NO. FROM-TO	INTERVAL		NO. FROM-TO	FLOAT COLLARS, ETC. - SPECIFY	

(S) 0'-300'	(5) 0'-300'	NONE		Guide shoe, float collar		Centralize bottom 3 joints then every 2 joints.
(I) 0'-2800'	(8) 2450'-2800'	NONE		Float shoe, float collar		Centralize bottom 4 joints, then every 2 joints.
(P) 0'-10,500'	(42) 7000'-10,500'	(35) 10,000'-10,500'	Float shoe, float collar			Centralize bottom 12 joints, then every 100' to 7000'. Scratchers, every 15' from TD to 10,000'. Float collar to be located 1 join above float shoe.

RECEIVED
MAR 20 1959
U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO