

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill, to deepen or plug well to a different reservoir.
Use "APPLICATION FOR PERMIT TO DRILL" for such proposals.)

1. NAME OF OPERATOR Jake L. Hamon		5. LEASE DESIGNATION AND SERIAL NO. NM 34457	
2. ADDRESS OF OPERATOR P. O. Box 663, Dallas, Texas 75221		6. IF INDIAN, ALLOTTEE OR TRIBE NAME NA	
3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1930' FSL & 690' FEL (NE SE) 1980		7. UNIT AGREEMENT NAME NA	
14. PERMIT NO. NA		8. FARM OR LEASE NAME Federal 35	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3280' Gr. 3296' KB		9. WELL NO. 1-22	
		10. FIELD AND POOL, OR WILDCAT d. Co + 12w 12e 8s Wildcat	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 33, T-20-S, R-26-E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input checked="" type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <input type="checkbox"/>	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- Spudded 3:30 P.M. 8/9/80.
- Drilled 17-1/2" hole to 350'. Ran 12 jts of 12-3/4", 35#, K-55 ST&C casing. Casing set at 350'. Cemented with 415 sks of Class C cement plus 2% CaCl. Cement circulated. Plug down at 4:30 P.M. 8/12/80.
- WOC 18 hrs. Installed bradenhead & BOP.
- Pressure tested casing and BOP to 1000 psi and held pressure for 30 minutes. Had no pressure loss.
- Prep to drill ahead with 11" hole.

18. I hereby certify that the foregoing is true and correct

SIGNED Scott H. Brubaker TITLE Petroleum Engineer DATE 8/14/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 27 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side