

Alameda, NM 88810

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED BY

JUN 28 1984

Form Approved.
Budget Bureau No. 42-R1424

5. LEASE

NM 0486

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Big Eddy Unit

8. FARM OR LEASE NAME
Big Eddy Unit

9. WELL NO.
79-Y

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA
Sec. 21, T21S, R28E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3238.6' KB

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ Plug Back

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

Box 2760, Midland, Tx 79702-2760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1930' FEL Unit Letter J.

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Plug back to Delaware ☒

& turn wellbore over to Yates Petroleum Co.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-13-84 MIRU Pulling Unit, Blew well down to pit.
Circulate 5½" Csg. w/10.0# mud laden BW.

6-14-84 Spotted 30 sx Class "H" cement plug @ 9500'-9320'
(1.18 Ft 3/sx, 15.6 ppg). POOH & Rig up to pull 5½" csg.
Ran freepoint. SDON.

6-15-84 Layed down 158 Jts. 5½" 17# N-80 LT&C casing.
Total - 6,653'.

6-16-84 RIH w/2-3/8" tbg. to 6700' for plug #2. Set plug
in 5½" (Top @ 6641') w/35 sx Class "H" cement 6700'-6578' (Yeild 1.18,15.6p
Pull of hole w/tbg. SDON & Sunday. (Over)

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED K.C. Hutchens

TITLE SR. PROD. CLERK

DATE JUNE 20, 1984

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL

JUN 28 1984

NEW MEXICO

*See Instructions on Reverse Side

Post ID-3
7-13-84
chp. 010

Post ID-2
7-13-84
RTH Atka

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-168

6-18-84 RIH w/ 2-3/8" tbg. Tagged plug @ 6,505'.
P00H & Layed down Tbg. Cut off csg. head.
RD pulling unit. Released wellbore to Yates Petroleum Corp.
Artesia, New Mexico 88210. 207 S. 4th.
Final Report For Perry R. Bass.