

5. LEASE DESIGNATION AND SERIAL NO.

NM 0486 RECEIVED BY

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

JUL 17 1984

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

79-Y

10. FIELD AND POOL, OR WILDCAT

Wildcat Delaware

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Unit J, Sec. 21-21S-28E

12. COUNTY OR PARISH

Eddy

13. STATE  
NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 S. 4th, Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement. See also space 17 below.)  
At surface

1980 FSL & 1930 FEL, Sec. 21-T21S-28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

3238.6' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Production Casing, Perforate

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-19-84 - Installed wellhead equipment.

6-20-84 - Rigged up pulling unit.

6-21-84 - Ran 154 jts of 5-1/2" 15.5# J-55 casing set 6508'. Guide shoe set 6508'. Float collar set 6465'. Cemented w/720 sacks Class "C" .6% CF-1, .2% AF-S and 5 bbls/sack salt. PD 4:00 PM 6-21-84. Bumped plug to 2200#, held for 30 minutes, float held okay. WOC 18 hrs.

6-26-84 - WIH and perforated 5784-5805' w/10 .50" holes as follows: 5784, 85½, 87, 91, 93, 95, 97, 5801, 03 and 05'.

6-28-84 - Treated perforations 5784-5805' w/2000 gal 15% NEFE acid.

7-3-84 - Frac'd perforations 5784-5805' w/21000 gal 70% Quality Foam, 15500# 20/40 sand and 500# 10/20 sand, N₂.

7-4-84 - Recovering load and swabbing well.

I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 7-5-84

(This space for Federal or State Records)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL

JUL 13 1984

Carlsbad

NEW MEXICO

\*See Instructions on Reverse Side