

U.S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C. 20250

FIELD REPORT FOR COMPLETION OF WELLS

Operator <i>Donnell</i>		Date <i>9-28-80</i>		Well # <i>1</i>	
Location <i>W-101</i>	Unit <i>E</i>	Section <i>SE</i>	Township <i>S15</i>	Range <i>27 E</i>	County <i>Edley</i>
Drilling Contractor <i>450/W</i> <i>900/W</i>			Type of Equipment <i>Rotary</i>		

x witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
	<i>12 1/4</i>			<i>100'</i>	<i>None</i>
	<i>10 3/4</i>	<i>40</i>		<i>3100'</i>	<i>None</i>
<i>8 5/8</i>	<i>6 1/2</i>	<i>17.20 - 23</i>		<i>15000'</i>	<i>We have a 9 5/8</i>

Casing Data:

Surface joints of inch = Grade

(Approved) (Rejected)

Inspected by date

Cementing Program

Size of hole *12 1/4* Size of Casing *10 3/4* Sacks cement required

Type of Shoe used *Guide* Float collar used *Insert* Rim Seal welded *yes*

Size of hole *3059* Se *3073* Feet of *10 3/4* *405* # *J-55*

3059 with *300* sacks needed around shoe

- *200* sack *Thick set* additives *+ 1900 SX Lite*

Plug down @ *8'00* (AM) (PM) Date *9-28-80*

Cement circulated *yes* of Sacks *100 SX*

Cemented by *Donnell* Witnessed by *B W Weaver*

Temp. Survey ran @ (AM) (PM) Date top cement

Casing test @ (AM) (PM) Date

Water Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Wellhead used Witnessed by

Notes: *Last Drilling Break 2948-2980 4 Centerline*

125% Excess + 200 SX Thick set