

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG-5995

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	RECEIVED SEP 18 1980 O. C. D. ARTESIA, OFFICE	7. Unit Agreement Name
2. Name of Operator Amoco Production Company		8. Farm or Lease Name Lancaster Spring Com.
3. Address of Operator P. O. Box 68 Hobbs, NM 88240		9. Well No. 1
4. Location of Well UNIT LETTER I, 2310 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 8 TOWNSHIP 22-S RANGE 26-E N.M.P.M.		10. Field and Pool, or Wildcat Und. Happy Valley Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3414.0 GL		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 2920' and ran 36# K-55 9-5/8" casing set at 2920'. Cemented with 400 SX Thix set cement with additives, 1400 SX 65/35 Pos. Life cement with additives, and with 200 SX Class C Neat cement. Circulated 900 SX. Plugged down at 5:30 p.m. 9-3-80. WOC 20.5 hr. Tested casing with 1500#. Test OK. Reduced hole to 8-3/4" and resumed drilling.

0+4-NMOCD, A 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou 1-Inexco  
1-Pogo Prod. 1-Cotton Pet. 1-Read X Stevens 1-Holly Energy 1-E. L. Latham

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Benton Green TITLE Assist. Admin. Analyst DATE 9-17-80

APPROVED BY W.A. Gussert SUPERVISOR, DISTRICT II DATE SEP 22 1980

CONDITIONS OF APPROVAL, IF ANY: