

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 13232

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government "AN" Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Winchester
Undes. Morrow11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3-T20S-R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mex.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

JUL 20 1981

2. NAME OF OPERATOR

CITIES SERVICE COMPANY /

3. ADDRESS OF OPERATOR

O. C. D.
ARTESIA, OFFICE

P. O. Box 1919 Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)At surface 660' FNL & 1980' FWL of Sec. 3-T20S-R28E, Eddy County,
New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3284' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

T. D. 425' Red Beds. Prep. to drill ahead. MIRU a rotary & spudded a 17-1/2" hole at 1100 MDT & drilled to a T.D. 425' in Red Beds. Ran & set 11 jts. (408.60') 13-3/8" OD 48# H40 csg. at 425' and cemented w/300 sx of Class C Thikset + 1/4# Flocele & 10# Gilsonite/sk + 300 sx of Class C + 1/4# Flocele & 2% CaCl₂ cement. Plug down at 0300 MDT 7-10-81. Circulated 150 sx to surface. WOC 18 hrs. Tested 13-3/8" csg. to 500# - OK.

RECEIVED
JUL 17 1981OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Reg. Oper. Mgr.-Drlg.

DATE 7-14-81

(This space for Federal or State Office use)

ROGER A. CHAPMAN

APPROVED BY
CONDITIONS OF

TITLE

DATE

JUL 17 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side