

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME BIG EDDY UNIT
2. NAME OF OPERATOR PERRY R. BASS	8. FARM OR LEASE NAME BIG EDDY UNIT
3. ADDRESS OF OPERATOR Box 2760 MIDLAND, TX 79702	9. WELL NO. 83
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FWL & 660' FNL, SEC. 10, T-21S, R-28E.	10. FIELD AND POOL, OR WILDCAT SAND POINT MORROW
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 10, T-21S, R-28E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3319' GL 3337' KB	12. COUNTY OR PARISH EDDY
	13. STATE N. MEX.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) SPUD DATE & SURFACE CSG.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

SPUD @ 3:14 PM CST 2-13-81.

COMMENCED DRILL. 15" SURFACE TO 1071' RAN 28 JTS. 11 3/4" 47# K-55 CSG. SET @ 1071', CEMENTED W/600 SKS "LITE" PLUS ADDITIVES TAILED W/200 SKS CLASS "C" PLUS ADDITIVES, PLUG DOWN @ 7:15 PM 2/16/81 CTS, FLOAT HELD CIRC 250 SKS. WOC 20 1/2 HRS. TEST BOP TO 1000# O.K.

DRILLED 10 5/8" HOLE TO 3107' RAN 69 JTS. 8 5/8" CSG. (58 JTS. 8 5/8" 28# S-80 ST&C CSG.) (11 JTS. 8 5/8" 32# K-55 ST&C CSG.) SET @ 3107' CEMENTED W/725 SKS. "LITE" PLUS ADDITIVES TAILED W/200 SKS. CLASS "C" PLUS ADDITIVES CIRC 370 SKS. TO PIT. DROP BOMB & OPEN DV TOOL. @ 1033' NO CIRC FLUID @ SURFACE, CEMENTED W/100 SKS. "LITE" PLUS ADDITIVES TAILED W/100 SKS. CLASS "C" PLUS ADDITIVES. BUMPED # PLUG TO 2500# PLUG DOWN @ 11:45 AM. 2/22/81. TEST BOP TO 5000# & HY DRILL TO 1500# DRILL DV TOOL & TEST TO 1000# HELD O.K. TEST CSG & SHOE.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. B. Murty, Jr.

TITLE

Sr. Prod. Clerk

DATE

May 5, 1981 OVER

(This space for Federal or State office use)

APPROVED BY

RODOLFO A. CHAMON

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAY 11 1981

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, floor or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-160

70 700 # H228 D.K.
COMMENTED DNLG. 7 7/8" HOLE. 2-23-81.