

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Perry R. Bass
3. ADDRESS OF OPERATOR
P. O. Box 2760, Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FEL, 660' FNL, Sec. 16, T20S, R31E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: As above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Spud, Surface Casing, Intermediate Casing



OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
E-264
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME RECEIVED
Big Eddy Unit
8. FARM OR LEASE NAME DEC 15 1981
Big Eddy Unit
9. WELL NO. O. C. D.
89 ARTESIA, OFFICE
10. FIELD OR WILDCAT NAME
Eddy Undesignated
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 16, T20S, R31E
12. COUNTY OR PARISH 13. STATE
Eddy New Mexico
14. API NO. UNKNOWN
15. ELEVATIONS (SHOW DF, KDB, AND WD)
GL 3461'

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 15" hole at 3:00 PM CST 10/31/81. Ran 15 jts 11-3/4" 42# H-40 ST&C casing to 650'. Cemented with 500 sxs Class "C" plus additives. PD at 7:45 PM CST 11/1/81. Float held.

Drilled 11" hole to 4618'. Ran 40 jts 8-5/8" 32# K-55 ST&C and 67 jts 28# S-80 ST&C with DV tool at 2639'. Cemented 1st stage with 700 sxs Lite tailed with 150 sxs Class "C" plus additives. Open DV tool and pumped 1800sxs Lite tailed with 100 sxs Class "C" + additives. Plug down at 12:30 PM CST 11/17/81.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNATURE

Lucien J. Jaquez Jr.

TITLE

PRODUCTION ENGINEER

12/11/81

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well, and date well site conditioned for final inspection looking to approval of the abandonment.