N M CCC					
Form 9–331 Dec. 1973	Form Approved. Budget Bureau No. 42–R1424	e de la companya de Provincio de la companya de la company Provincio de la companya de la compa			
C/ S <sup>Y</sup> UNITED STATES	5. LEASE				
DEPARTMENT OF THE INTERIOR	_ NM-25692				
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME				
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME FEB 2 7	981			
1. oil gas γγ	Federal BR Com.				
well well well other	9. WELL NO. O. C. D.				
2. NAME OF OPERATOR	ARTESIA, OF	t. E			
Amoco Production Company	10. FIELD OR WILDCAT NAME				
3. ADDRESS OF OPERATOR	Wildcat Morrow				
P. O. Box 68 Hobbs, NM 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA				
below.) AT SURFACE: 1102' FWL & 1980' FSL					
AT TOP PROD. INTERVAL: (Unit L, SW/4, SW/4)	12. COUNTY OR PARISH 13. STATE				
AT TOTAL DEPTH:	EddyNM				
16 OUFOK ADDODDIATE DOV TO INDIGATE NATION OF HERE	14. API NO.				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
	15. ELEVATIONS (SHOW DF, KDB, AND WD)				
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4242.8' GL				
TEST WATER SHUT-OFF					
FRACTURE TREAT					
SHOOT OR ACIDIZE					
PULL OR ALTER CASING	(NOTE) Report results of multiple competition or zone (change on Form 9–330.)				
CHANGE ZONES	U.S. GEOLOGICAL SURVEY				
ABANDON*	ROSWELL, NEW MEXICO				
(other)					

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 1-30-81, Abbot Brothers Drilling, spudded a 17-1/2" hole at 12:00 a.m. with cable tools and drilled to a TD of 98'. On 2-8-81, MGF Drilling Co. (Rig #23) commenced drilling with rotary tools. Drilled to a TD of 303' and ran 13-3/8" 48# H-40 casing set at 303'. Cemented with 300 SX Class "C" cement with 1% CACL. Plugged down 12:00 p.m. 2-9-81. Circulated 40 SX. WOC 18 hrs. Tested casing at 500# for 30 min. and held OK. Reduced hole to 12-1/4" and resumed drilling.

0+5-USGS, A	1-Hou	1-Susp	1-W. S	tafford,	Hou	1-GLF	
Subsurface Safet	ty Valve: Manu. and Type					. @	Ft.
18. I hereby cert	ify that the foregoing is true		. Analyst	DATE	2-1	9-81	-
APPROVED BY CONDITIONS OF A	ACCEPTED FOR RECC <u>PETER W. CHEST</u> PPROVAL, IF ANY: FEB 2 5 1981	RE page for Federal	or State office us	ie)	-		
	U.S. GEOLOGICAL SU ROSWELL, NEW MEX	RVEY IGGee Instructions of	on Reverse Side				