Form 9–331 Dec. 1973	Form Approved. Budget Bureau No. 42–R1424	c15F
UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	NM-25692	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME	
	Federal BR Com.	
1. oil gas well well 🕅 well 🕅 other		
2. NAME OF OPERATOR		
Amoco Production Company	10. FIELD OR WILDCAT NAME. C. D.	•
3. ADDRESS OF OPERATOR	Wildcat Morrow C. D.	
P. O. Box 68 Hobbs, NM 88240	Wildcat Morrow ARTESIA OF ARTESIA	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA <b>2</b> 30-22- <b>3</b>	
AT SURFACE: 1980' FSL & 1102' FWL	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: (Unit L, ₩W/4, SW/4) AT TOTAL DEPTH:	Eddy NM	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.	
REPORT, OR OTHER DATA		
	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4242.8' GL	A SMALLER
FRACTURE TREAT	- CORE IN	
	511/29	
REPAIR WELL	2 (Norig Report results of multiple completion or zone changed on Form 9-330.)	
PULL OR ALTER CASING	2 change on Form 9-330.)	
MULTIPLE COMPLETE	NL & GAS	
	NUL GAS SURVEY	÷
(other)		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statisticluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	irectionally drilled, give subsurface locations and it to this work.)*	
Drilled to a TD of 10000'. Encountered no o After receiving verbal approval from Peter ( telecon Larry Sheppard, Amoco 3-14-81) well procedure:	Chester, USGS Roswell, (per	
Spotted a 150' cement plug (75 sacks Class H Neat) from 9575'-9425'. Spotted a 150' cement plug (75 sacks Class H Neat) from 6315'-6165'. Spotted a 100' cement plug (45 sacks Class H Neat) from 3175'-3075'. Spotted a 100' cement plug (45 sacks Class H Neat) from 2080'-1980'. Set a 35' surface plug and installed P X A marker.		
0+4-USGS, A 1-Hou 1-Susp 1-LBG	1-W. Stafford, Hou	
Subsurface Safety Valve: Manu. and Type	Sat @ 54	
A	Ft.	
18. I hereby certify that the foregoing is true and correct		
SIGNED _ PEnton Are TITLE Ast. Adm. And	alyst <sub>date</sub> 3-18-81	
(This space for Federal or State off	ice use)	
APPROVED BY	DURCES L. 29-59	·
CONDITIONS OF APPROVAL, IF ANY:	DATE Cart	
	MAR 1 9 1931	
*See Instructions on Reverse S		
	U.S. GEOLOGICAL SURVEY	

•

ARTESIA, NEW MEXICO