

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION **RECEIVED**

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

MAY 8 1981

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

L-6368

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name Lancaster Spring Com.
3. Address of Operator P. O. Box 68 Hobbs, NM 88240	9. Well No. 2
4. Location of Well UNIT LETTER <u>K</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>9</u> TOWNSHIP <u>22-S</u> RANGE <u>26-E</u> N.M.P.M.	10. Field and Pool, or Wildcat <u>Und. Happy Valley Morrow</u>
11. Elevation (Show whether DF, RT, GR, etc.) 3353.6' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 3-27-81, Warton Drilling Co. (Rig #3) spudded a 17-1/2" hole and drilled to a TD 726'. Ran 705' of 13-3/8" 48# H-40 casing and set at 726'. Cemented with 300 sacks Thixset with 7-1/4" Celloflake followed by 650 sacks Class 'C' with 1% Ar7. Plug down at 5:00 p.m. 3-28-81. Cement did not circulate. WOC 6 hrs. Ran temperature survey. TCMT 440'. Ran 1" to 430' and cemented with 450 sacks Class C with 1% CACL. Reduced hole to 12-1/4" and resumed drilling.

0+5-NMOCD, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-GPM

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Greg Mitchell TITLE Admin. Analyst DATE 5-6-81

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: