Base 1997 Dudget Rureau No. 42-R1424 UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUBDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS S. FARE Cont on 2 bits of the to presonable MAY 2 5 100 1. of methy to presonable Other DRY HOLE 2. RAME OF OFFRATOR MAY 2 5 100 Rarvey L. Nates Company / ADDECSS OF OFFRATOR P O. Day 1933 . Roswell 1, N. M. B8201 DECATION OF WELL (REPORT LOCATION CLEARLY See space 17 below) A DORTON OF WELL (REPORT LOCATION CLEARLY See space 17 below) 1985' FSL & 430' FAIL AT TOP PROPONIATE DOX TO INDICATE NATURE OF NOTICE THE AND SURVEY OR AARA 18. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE SUBSEQUENT REPORT OF 19. OF THER TAT SAME 19. OF ALL CASE ADDIC ADTA SUBSEQUENT REPORT OF 19. DESCRIBE PROPOSED OR COMPLETED OFFICIATIONS (Clearly state all pertinent during and proposed work. If well is directionally difficult, give Appendix during and proposed work. If well is directionally difficult, give Appendix during and proposed work. If well is directionally difficult, give Appendix during and proposed work. If well is directionally difficult, give Appendix during and proposed work. If well is directionally difficult, give Appendix during and proposed work. If well is directionally difficult, give Appendis and there were appending ton the were append			Y - tartato () SF	ine senite
UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS One at use the form by proposed to 0 fill or the deepen or plug hack to a different well dependent of proposed to 0 fill or the deependent plug hack to a different Harvey E. Yates Company / 3. ADDRESS OF OPERATOR P O. Box 1933 - Roswell, N.M. 88201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 Nation of Well (REPORT LOCATION CLEARLY. See space 17 Nation of Well (REPORT LOCATION CLEARLY. See space 17 A TOPA PROPON INTERVEX: SAME AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE: REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF DEFENTIONS (Clearly state all pertinent deals, and ever the dates, including seturated deepts for all matters and zones pertinent deals, and ever there there of stating any proposed work. If well is directionally diffied, was there will be a state and proposed work. If well is directionally diffied, was there will be a state and proposed work. If well is directionally diffied, was there and comes will be there will be a state of any proposed work. If well is directionally diffied, was there will be a state of any proposed work. If well is directionally diffied, was there and comes pertinent of this work.) ² 4/20/81 1. Mix & pump 35 size C1 "C" cement w/2Z CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 size cement plug @ surface 6. All plugs will be placed thru tubic for the come of Co. & a dry hole marker installed thru tubic for the come of Co. be a dry hole marker installed thru tubic for Denton Cement Co. be a dry hole marker installed thru tubic for the state of any come of the come of the state of any come of t	Farm 9-331 Dec. 1973		Form Approved. Budget Bureau No. 42–R1424	
GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS Base add use the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to endown or plug back to a different difference the form inty propriate to back and bac		UNITED STATES	5. LEASE	612
GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME Con out we this form to propherable to did out of the opponent of physical to a different were out of the propherable to did out of the opponent opponent of the opponent of the opponent o	DEPARTN	VENT OF THE INTERIOR	LC-063567	ŀ
SUNDRY NOTICES AND REPORTS ON WELLS Our of use the form to proceed to child our deserver of the additional to the form to proceed to child our deserver. MAY 2 ± 10000000000000000000000000000000000	GE	OLOGICAL SURVEY		
 1. oil gest other DRY HOLE 2. NAME OF OPERATOR Harvey E. Yates Company / 3. ADDRESS OF OPERATOR P. O. Box 1933, Roswell, N.M. 88201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1985' FSL & 430' FML AT SURFACE: AT TOP PROD. INTERVAL: AT TOP PROP. INTERVAL: SAME 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TRAT YHEL CHAPTER COMPLETED OPERATIONS (Clearly state all pertinent of Ms. on OFF ALL MAY 18 1981) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent of Ms. on OFF ALL MAY 18 1981) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent of Ms. on OFF ALL MAY 18 1981) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent of Ms. on OFF ALL MAY 18 1981) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent of Ms. on OFF ALL MAY 18 1981) 18. MAY 18 1981 19. Mix & sport 35 sxs C1 "C" cement w/22 CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 676' to 423' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & splace 10 sx cement plug @ surface 6. All plugs will be placed thru tubited to the strate of the ward of the ward of the ward of the ward of the complexity of the perton Co. & a dry hole marker installed 			Iferent MAY 2330	
 weil L1 weil L1 other DRY BOLE 2. NAME OF OPERATOR Harvey E. Yates Company / 3. ADDRESS OF OPERATOR P. O. Box 1933, Roswell, N.M. 88201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1985' FSL & 430' FML AT SURFACE: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUTOFF CHARGE SONES ABANDON* COMPLETED OPERATIONS (Clearly state all pertinent delays, and ever Generate Hocations and measured and true vertical depths for all markers and zones pretinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaCl plug from 776' to 676' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 323' to 5'. Mix & spot 10 ppg mud from 323' to 5'. Mix & spot 10 ppg mud from 578' to 423'. Mix & spot 10 ppg mud from 578' to 423'. Mix & spot 10 ppg mud from 323' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. Mix & spot 10 ppg mud from 578' to 5'. 	reservoir. Use Form 9-331-C fo	r such proposals.)		
 1-Y 1-1- 1-	1. oil gas	other DPV HOLE	McMillan Scarp	
 2. MARE OF OPERATOR Harvey E. Yates Company / 3. ADDRESS OF OPERATOR P. O. Box 1933, Roswell, N.M. 88201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT SURFACE: AT TOP PROD. INTERVAL: SAME AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent dists, and end of the space of form 9 and the space of form 9 and the space of the soft of all markers and zones pertinent to this work.)* 4/20/81 1. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tuping Denton Cement Co. & a dry hole marker installed 	the second		1-Y ABTERIAL OPACE	ni di
 3. ADDRESS OF OPERATOR POBOX 1933ROSWell, N.M. 88201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1985' FSL & 430' FWL AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: SAME AT TOTAL DEPTH: SAME G. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT. OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: LEVATIONS (SHOW DF, KDB, AND WD) 3343.46' GR SLEVATIONS (SHOW DF, KDB, AND WD) 3343.46' GR (NOTE: Report results of multiple construction of the mathematication of the state all pertinent details, and one for a state of the state all pertinent details, and one for the state of the sta	Harvey E. Yate	es Company /		ļ.
 P. O. Box 1933 - Roswell, N.M. 88201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1985' FSL & 430' FML AT SURFACE: AT TOP PROD. INTERVAL: SAME AT TOP PROD. INTERVAL: SAME AT TOP ADDEPTH: SAME 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT. OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3343.46' GR REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: REPAIR WELL PULL OR ALTER CASING CHANGE ZONES ABANDON* XI I7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent duals, and are stating any proposed work. If well is directionally drilled, give by start at locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 576' to 423' Mix & spot 10 ppg mud from 52' to 5' Mix & place 10 sx cement plug @ surface All plugs will be placed thru tubits to Denton Cement Co. & a dry hole marker installed 				
 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1985' FSL & 430' FWL AT SURFACE: AT SURFACE: AT SURFACE: SAME AT TOP PROD. INTERVAL: SAME SAME 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF TEST WATER SHUT-OFF Hard State and PROVAL TO: SUBSEQUENT REPORT OF: Change on Form 9-apply 100 and 50 and matching any proposed work. If well is directionally drilled grows but write the and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 Mix & pump 35 sxs C1 "C" cement w/2% CaCl & spot plug from 776' to 676' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 10 ppg mud from 323' to 5' Mix & place 10 sx cement plug @ surface All plugs will be placed thru tub for Denton Cement Co. & a dry hole marker installed 				
AT SURFACE: AT TOP REOD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3343.46' GR IS. ELEVATIONS (SHOW DF, KDB, AND WD) 3343.46' GR IS. ELEVATIONS (SHOW DF, KDB, AND WD) 343.46' GR INTER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES MULTIPLE COMPLETE CHANGE ZONES IS. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent duals, and constructions and measured and true vertical depths for all markers and zones pertinent to this work.)' 4/20/81 1. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 576' co 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubier of Dente Constructions and the surface A Structure of the surface of the surface A dry hole marker installed	4. LOCATION OF WELL	(REPORT LOCATION CLEARLY. See space	ce 17 AREA	
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON* (cther) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and cover articleres date of stating any proposed work. If well is directionally drilled, give a bytertate locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaC1 & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 676' to 423' 4. Mix & spot 10 ppg mud from 578'' csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubited of the surface o		1985' FSL & 430' FWL	Sec. 6, T-20S, R-27E	
AT TOTAL DEPTH: SAME 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA Id. API NO. 14. API NO. 14. API NO. REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF Image: Subsequent REPORT OF: TEST WATER CASING Image: Subsequent REPORT OF: WULTIPLE COMPLETE Image: Subsequent REPORT OF: TO DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and compositions and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubing the Denton Cement Co. § a dry hole marker installed		RVAL:		ins parties
 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3343.46'. GR 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3343.46'. GR 16. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent duals, and the stating any proposed work. If well is directionally drilled, give the state of elevations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 19. Mix & spot 10 ppg mud from 676' to 423' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubing and prometice. 		SAME		
REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	16. CHECK APPROPRIATE	BOX TO INDICATE NATURE OF NO		1
 REQUEST FOR APPROVAL 10: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF [e.
 TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE GEPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent dtails, and cos Survey on a Get survey including estimated date of starting any proposed work. If well is directionally drilled, give subservate locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 35 sxs C1 "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubiter. 			3343.46' GR	
 FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* X (other) ID ESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent duals, and government duals, a	•	L TO: SUBSEQUENT REPORT O		
 SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING PULL OR ALTER CASING CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent duals, and gove of themet dates, including estimated date of starting any proposed work. If well is directionally drilled, give and gove of themet dates, and gove of the dates, and the date date of the dates date date date date date date date date				
 PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and cover primeried dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsertate locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaC1 & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 35 sx C1 "C" cement w/2% CaC1 plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubits for Denton Cement Co. & a dry hole marker installed 				
 MULTIPLE COMPLETE CHANGE ZONES ABANDON* I7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and out of frugent Quates, including estimated date of starting any proposed work. If well is directionally drilled, give subservate locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 35 sx C1 "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubile to perton Cement Co. & a dry hole marker installed 				17/530
 CHANGE ZONES ABANDON* I7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and one of pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give support dates, including estimated date of starting any proposed work. If well is directionally drilled, give support dates, and one of pertinent dates, and one of pertinent dates, and one of pertinent dates, and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 35 sx C1 "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubiled the placed thru tubiled to be placed to				
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and the of starting any proposed work. If well is directionally drilled, give supportate locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 35 sx C1 "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubiate at Denton Cement Co. & a dry hole marker installed 			1081	1
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and the of starting any proposed work. If well is directionally drilled, give supportate locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 35 sx C1 "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubiate at Denton Cement Co. & a dry hole marker installed 			MAY 18 1901	*
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent ditars, and good pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give publicate locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4/20/81 1. Mix & pump 35 sxs C1 "C" cement w/2% CaCl & spot plug from 776' to 676' 2. Mix & spot 10 ppg mud from 676' to 423' 3. Mix & spot 35 sx C1 "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubing to Denton Cement Co. & a dry hole marker installed 			IIIN ON SUBVET	
 to 676' Mix & spot 10 ppg mud from 676' to 423' Mix & spot 35 sx Cl "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' Mix & spot 10 ppg mud from 323' to 5' Mix & place 10 sx cement plug @ surface All plugs will be placed thru tubits for Denton Cement Co. & a dry hole marker installed 	including estimated o	ate of starting any proposed work, it w	ly state all pertinent details, and give pertiment dates, ell is directionally drilled, give subsurface locations and	
 Mix & spot 35 sx Cl "C" cement w/2% CaCl plug from 423' to 323'. 50' in and 50' out of 8 5/8" csg set @ 373' Mix & spot 10 ppg mud from 323' to 5' Mix & place 10 sx cement plug @ surface All plugs will be placed thru tubing to Denton Cement Co. & a dry hole marker installed 	to 6	76'		
 50' in and 50' out of 8 5/8" csg set @ 373' 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubics a Denton Cement Co. & a dry hole marker installed 				
 4. Mix & spot 10 ppg mud from 323' to 5' 5. Mix & place 10 sx cement plug @ surface 6. All plugs will be placed thru tubite hy Denton Cement Co. & a dry hole marker installed 				E
 Mix & place 10 sx cement plug @ surface All plugs will be placed thru tubing to Denton Cement Co. & a dry hole marker installed 				
6. All plugs will be placed thru tubics a Denton Cement Co. & a dry hole marker installed				
& a dry hole marker installed	$\begin{array}{c} \mathbf{J} \cdot \mathbf{M} \mathbf{X} \\ 6 \mathbf{A} 1 1 \end{array}$	a place to sx cement plug a plugs will be placed thru t	tubient Denton Cement Co.	
			175ET 1111	
Subsurface Safety Valve: Manu. and Type MAY 20 1981 SUN Set @ Ft. 18. I hereby certify that the foregoing is true and content of FE ATA FE				
Subsurface Safety Valve: Manu. and Type MAY 20 190 DIVISION Set @ Ft. 18. I hereby certify that the foregoing is true and correct USER VATION FE		Collection of the second se	1081	
Subsurface Safety Valve: Manu. and Type MAY Set @ Ft. 18. Thereby certify that the foregoing is true and correct Ft.		5012211 2	NUISIN DEL O	
18. I hereby certify that the foregoing is true and content	Subsurface Safety Valve: I	Manu, and Type	Set @ Ft.	
	18. I hereby certify that th	he foregoing is true and correct	RVA! FE	
HILE STINGET DATE 5/13/81	the T-		DATE 5/13/81	
SIGNED TITLE TOUTINEET DATE STISTOT	-			
AI-PROVED (This space for Federal or State office use)		-PROVED (This space for Federal or)	State office use)	
APPROVED BY Roger a. Chapmant TLE DATE	APPROVED BY	L a. Chapman TILE	DATE	F
CONDITIONS OF APPROVAL, IF ANY:		•		
MAY 1 8 1981				
La LANTE A CLUMAM	M	QA T 8 1881		
See Instructions on Reverse Side		ΔΥ 1 8 1981		