

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator TENNECO		Lease ST. FP 13 CO		Well # 2	
Location of Well	Unit E	Section 13	Township 21	Range 25	County Eddy
Drilling Contractor	Parker Drilling		Type of Equipment ROTARY SPUD 4/23/81		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
12 1/4"	8 5/8"	32 #	NEW	2200'	CIRC.

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole **12 1/4"** Size of Casing **8 5/8"** Sacks cement required **1500**

Type of Shoe used **Guide** Float collar used **YES** Btm 3 jts welded **YES**

TD of hole **2200** Set **2209** Feet of **8 5/8** Inch **32** # Grade **K-55**

New-used csg. @ **2200'** with **200** sacks neat cement around shoe **C.I.C 2% CaCl.**

+ **200** sax **C.I.C Thickset w/5% additives 1/4# Flocele, 2% CaCl + 400 sxs. H.L. 1/4# Flocele, 2% CaCl**

Plug down @ **3:00** (AM) (PM) **PM** Date **5/5/81**

Cement circulated **NO** No. of Sacks _____

Cemented by **HALLIBURTON** Witnessed by **Larry Brooks**

Temp. Survey ran @ **9:00** (AM) (PM) **PM** Date **5/5/81** top cement @ **400'**

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: **Lost circ @ 434' 8 CENT. 1 on shoe jt., & 1 on every 8th jt.**

2 BASKETS: RAN 1 BASKET ON 25th jt., 2nd @ 382'

1) RAN 1" to 410, tagged cmt. Pumped 35 sxs. C.I.C. 4% CaCl

2) TAGGED AT 380', pumped 35 sxs. C.I.C 4% CaCl.

3) " " 372' " 50 " " " " "

4) " " 318' " 130 sxs. C.I.C. 4% CaCl, Circ. 15 sxs. to the pit.