

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<b>SUNDY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</small>		<b>RECEIVED</b> JUN 01 1981	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
1. OIL <input type="checkbox"/> WELL GAS <input checked="" type="checkbox"/> WELL OTHER-		5. State Oil & Gas Lease No. K-4902	
2. Name of Operator TENNECO OIL COMPANY		6. Farm or Lease Name State FP-13 Comm	
3. Address of Operator 6800 Park Ten Blvd., San Antonio, Texas 78213		7. Unit Agreement Name	
4. Location of Well UNIT LETTER <u>AE</u> 990 FEET FROM THE <u>West</u> LINE AND <u>2310</u> FEET FROM THE <u>North</u> LINE, SECTION <u>13</u> TOWNSHIP <u>21</u> RANGE <u>25</u> N.M.P.M.		8. Well No. 2	
5. Elevation (Show whether DF, RT, GR, etc.) 3291.8' (GR)		9. Field and Pool, or Wildcat Catclaw Draw Morrow	
12. County Eddy			

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/6/81

Ran & cemented 50 jts of 8-5/8" 35 K-55 8<sup>rd</sup> set @ 2203'. Cemented w/200 sx Thix-set +2% CaCl<sub>2</sub> + 5# gilsonite + 1/2 # Floccile/sx followed w/400 sx Howcolite + 2% CaCl<sub>2</sub> + 5# Gilsonite + 1/2# Floccile/sx followed by 300 sx This-set + 400 sxs Lite + 200 sx Class "C" + 2% CaCl<sub>2</sub> + 1/2 # floccile/sxs. Pumped plug down w/water. Plug down @ 11:00 a.m. w/1150 psi date 5-5-81. Cemented thru 1" into 12 5/8" annulus w/250 sxs Class "C" cement w/4% CaCl<sub>2</sub> in 4 stages. Brought good cement to surface. WOC - 39 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mary Hall TITLE Production Analyst DATE 5/12/81

APPROVED BY M. Williams TITLE OIL AND GAS INSPECTOR DATE JUN 10 1981

CONDITIONS OF APPROVAL, IF ANY: