

UN ED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPL

NM OIL CONS. COM. 100-
Drawer DD
Artesia, NM 88210

Form approved.
Budget Bureau No. 42-R355.6.

5. LEASE DESIGNATION AND SERIAL NO.

NM-911

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Federal

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Avalon (Morrow)

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 2, T-21-S, R-26-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1a. TYPE OF WELL:

OIL WELL ☐

GAS WELL ☒

DRY ☐

Other

b. TYPE OF COMPLETION:

NEW WELL ☒

WORK OVER ☐

DEEP-EN ☐

PLUG BACK ☐

DIFF. RESVR. ☐

Other

2. NAME OF OPERATOR

David Fasken

OIL & GAS

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

3. ADDRESS OF OPERATOR

608 First National Bank Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

2530' FEL & 2430' FNL

At top prod. interval reported below

At total depth

14. PERMIT NO.

ARITE-1558

15. DATE SPUDDED

7-4-81

16. DATE T.D. REACHED

8-24-81

17. DATE COMPL. (Ready to prod.)

9-5-81

18. ELEVATIONS (DF, BBL, RT, OR, ETC.)*

3291.6' GL

19. ELEV. CASINGHEAD

3293

20. TOTAL DEPTH, MD & TVD

11,209'

21. PLUG, BACK T.D., MD & TVD

11,096

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

A-11

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

10,858-10,893' ---Morrow Sand

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

CNL-LDT, D.L.L., N.G.T., Dipmeter

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	54.5, 61.00	396'	17 1/2"	300 Lite+100G+4yds. ready-mix	-0-
8-5/8"	24, 32	3003'	12 1/2"	1000 Lite+ 300thixset+ 808C	-0-
4 1/2"	11.6, 13.5	11,209'	7-7/8"	550 Trinity-Lite+850H+1000+Trinity Lite+1000 Out by @ 6912'	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	10,356'	10,343'

31. PERFORATION RECORD (Interval, size and number)

10,858'-10,881' -.25" hole entry-24 holes

10,889'-10,893' -.25" hole entry - 5 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
	None

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
9-4-81		Flowing				S.I.	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
9-8-81	24	9/32"	→	-0-	1146	-0-	---
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
575	Pkr	→	-0-	1146	-0-	---	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented

ROGER A. CHAPMAN

TEST WITNESSED BY

Mike Davis

35. LIST OF ATTACHMENTS

Deviation Survey, Form 9-331 & N.M.O.C.C. Forms C-102 & C-122

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

S. L. Parks

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

DATE 9-17-81

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sticks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Delaware	2300'	4486'				
Bone Springs Lime	4486'	5390'				
st. Bone Springs						
and	5390'	5938'				
id. Bone Springs						
and	5938'	7994'				
id. Bone Springs						
and	7994'	8560'				
Blfcamp	8560'	9330'				
nyon	9330'	9812'				
rawn	9812'	10,028'				
oka	10,028'	10,647'				
orrow	10,647'	10,961'				
arnett Shale	10,961'					

38.