

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well      gas ☐ well      other ☐
- 
2. NAME OF OPERATOR  
Bliss Petroleum, Inc. /
- 
3. ADDRESS OF OPERATOR  
P.O. Box 1817      Hobbs, n.M.      88240
- 
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE:      Unit L, 2310' FSL & 330' FSL,  
AT TOP PROD. INTERVAL:      Sec. 22, T20S, R29E  
AT TOTAL DEPTH:
- 
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

### TEST WATER SHUT-OFF

## FRACTURE TREAT

## SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

**MULTIPLE COMPLETE**

## CHANGE ZONES

**ABANDON\***

(other)

Ran 8 5/8" Surface Casing.

SUBSEQUENT REPORT OF

AUG 18 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
NM 13995
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
REC'D
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
DB Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Undesignated
11. SEC., T., R., M., OR BLK. AND SURVEY OR  
AREA  
Sec. 22 - T20S - R29E
12. COUNTY OR PARISH | 13. STATE  
Eddy | N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3274' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well at 11:00 A.M. on 7-30-81.

Ran:	1 - Halliburton 8 5/8" Guide Shoe	1.10'
	3 jts - 8 5/8", 24#, J-55, Casing, New, ST&C	110.20'
	5 jts - 8 5/8", 20#, J-55, Casing, New, ST&C	167.75'
	Total	279.05'

Top Csg. Set at GL 279.05'. Cemented w/ 300 sx.

class "H" cmt. w/ 2% CaCl<sub>2</sub> & 1/4 #/sx. Flocele. TOC by Temp. Survey at 150'.  
Filled 8 5/8" & OH annulus w/ 11 yards ready mix concrete to surface. Plug down.  
at 1:30 A.M. on 8-2-81.

**Subsurface Safety Valve: Manu. and Type** \_\_\_\_\_ **Set @** \_\_\_\_\_ **Ft.**

**18. I hereby certify that the foregoing is true and correct**

**SIGNED**

**TITLE**

President

DATE \_\_\_\_\_

8-14-81

APPROVED BY  
CONDITIONS

ACCEPTED FOR RECORD (This space for Federal or State office use)  
ROGER A. CHAPMAN

# TITLE

DATE \_\_\_\_\_

AUG 24 1981

U.S. GEOLOGICAL SURVEY.  
ROSSELL, NEW MEXICO.

**See Instructions on Reverse Side**