Form 9-331 (May 1963) DEPAR	UNIT STATES TMENT F THE INTER	70ther Instructions	Form approved. Budget Bureau No. 42-R1424.  5. LEASE DESIGNATION AND SERIAL NO.
	GEOLOGICAL SURVEY	Artesia, NM 88210	NM-911
	OTICES AND REPORTS posals to drill or to deepen or plug iCATION FOR PERMIT—" for such	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1. OIL GAS WELL X OTHER	Drilling Well		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR			8. FARM OR LEASE NAME
David Fasken			El Paso Federal
3. ADDRESS OF OPERATOR			9. WELL NO.
4. LOCATION OF WELL (Report location See also space 17 below.) At surface	Bank Bldg., Midland, n clearly and in accordance with an	y State requirements.*  SEP 2 2 1031	10. FIELD AND POOL, OR WILDCAT  AVAION (MOTTOW)  11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA
1582' FNL & 1991'	FWL of Sec. 2		Sec. 2, T-21-S, R-26-E
14. PERMIT NO.	15. ELEVATIONS (Show whether I 3202.2 GL	OF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE Eddy New Mexico
16. Check	Appropriate Box To Indicate	Nature of Notice, Report, or	Other Data
NOTICE OF INTENTION TO:			QUENT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other) Cement Ca	
(Other)		Completion or Recom	its of multiple completion on Well opletion Report and Log form.)
17. DESCRIBE PROPOSED OR COMPLETED proposed work. If well is dire nent to this work.) *	OPERATIONS (Clearly state all pertine ectionally drilled, give subsurface loc	ent details, and give pertinent date eations and measured and true vert	es, including estimated date of starting any ical depths for all markers and zones perti-
-6-81 and 72 jts. 8-5 & 1394'. Cemented 12.7 ppg, yield ppg, yield 1.50 plug down @ 3:Pl T/C inside 12½" 3 stages w/265	/8" 24# & 32#/ft. ST&ded with 1000 sx Hallil 1.84 cf/sk + 300 sx cf/sk.+160 sx Class of M 9-6-81. No returns of x 8-5/8" annulus @ 60 sx Class C cement. off 8-5/8" csg. N.U.	C J-55 csg - set @ 29 burton Lite w/½# floc thixset w/½# flocele/C w/2% CaCl-slurry wt while cementing. WOC 60'. Cemented to surf	shoe, 1 float collar and 192'. Cement baskets @ 1352's cele/sk & 2% CaCl-slurry wt. 14.8 k & 2% CaCl-slurry wt. 14.8. 14.8 ppg, yield 1.32cf/sk 5 hrs. ran temperature surve face through 1" pipe in 19tal, test BOP & casing to
			ECE(72年)] SEP 21 1981
			OIL & GAS S. GEOLOGICAL SURVEY OSWELL, NEW MEXICO
18. I hereby certify that the foregoin	//	* -	
SIGNED	TITLE	. L. Parks, Agent	DATE 9-17-81
(This space for Federal or State	office use) MAN		
APPROVED BYCONDITIONS OF APPROVAL, I			DATE

\*See Instructions on Reverse Side