

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

31. Perforation Record 1-9/16 tbg gun w/ JRC SSB-II w/ steel Port Plugs. Perf @ 10,041'-10,044' (4 shots) & @ 10,134'-10,149' w/ (16 shots). Total of 20 holes.	32. Depth Interval 10,041'-10,149'	Amount & Kind of Material Used 10,250 Gals. 2890 HCl Acid & 16,000# 100 mesh Sand.
---	---	--

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	34. GEOLOGIC MARKERS
				NAME
				MEAS. DEPTH
				TRUE VERT. DEPTH
Delaware	3872'	3894'	NO CORES NO DST'S	3052'
Delaware	3940'	3955'	Limestone & Sand	6574'
Delaware	3970'	3981'	Limestone & Sand	9896'
Delaware	4081'	4153'	Limestone & Sand	11007'
Wolfcamp	10134'	10144'	Shale & Limestone	11302'
Morrow	12202'	12252'	Sand & Limestone	11867'
Morrow	12514'	12534'	Sand	
Morrow	12559'	12572'	Sand, Shale & Limestone	
Morrow	12602'	12640'	Sand & Limestone	