

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☐ gas well ☒ other ☐ JUL 1 1982
2. NAME OF OPERATOR THE PETROLEUM CORPORATION
3. ADDRESS OF OPERATOR O. C. D. Midland, Tx.
ARTESIA, OFFICE
One Marienfeld Place, Suite 555 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660/S 1980/W
- AT SURFACE: 3274.4'
- AT TOP PROD. INTERVAL: 7902.6'
- AT TOTAL DEPTH: 8325.6'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- | | |
|----------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> |

(other) Subsequent report of running
and cementing 8 5/8" casing

RECEIVED
JUN 4 1982
(NOTE: Reproduction of this document is prohibited without the written permission of the FBI.)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Ran 909' 24#/ft. and 2196' of 32#/ft. casing (8 5/8") Set at 3105'.
2. Cemented first stage with 200 sacks HLW + 5# Gilsonite + 5# Salt tailed by 400 sacks Class C + 1/4# Flocele + 2% CaCl_2 . 2nd stage - 950 sacks HLW + 5# Gilsonite + 5# Salt tailed by 150²sacks Class C + 2% CaCl_2 , did not circulate.
3. Ran cement bond log, top of cement at 745'. Perforated at 745'. Cemented with 550 sacks HLW + 5# Gilsonite + 5# Salt tailed by 300 sacks Class C + 4% CaCl_2 , circulated cement.

Subsurface Safety Valve: Manu. and Type none Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John Cox TITLE District Manager DATE 6-2-82

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

DATE _____

ACCEPTED FOR RECORD

***See Instructions on Reverse Side**

ML JUN 30 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO