

4/SF

NEW OIL CONS. COMMISSION  
Drawer DD  
Artesia, NM 88210

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒  
well well other

2. NAME OF OPERATOR

Texas Oil & Gas Corp.

3. ADDRESS OF OPERATOR

900 Wilco Building - Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 660' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) set casing string

5. LEASE NM 0554771  
Williamson

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Williamson Federal "A" Federal

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

East Burton Flat - Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 16, T-20-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

30-015-23995

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3272.6' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
MAR 26 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 2-14-82, drilled out of intermediate casing with a 7 7/8" bit. TD'd 7 7/8" hole at 11,876' on 3-12-82. Ran 70 joints of 4 1/2", 11.6#, S-95, LT&C and 204 joints of 4 1/2", 11.6#, N-80, LT&C production casing and landed at 11,876'. Cemented with 300 sacks of Class "H" w/5#/sx KCL & additives. Plug down at 7:00 PM on 3-15-82. Ran CCL & CBL logs on 3-22-82 and found top of cement at 10,697'. Prepare to move in completion unit.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carlton J. Beatty TITLE Drilling Engineer DATE 3-27-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

MAY 7 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO