

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0554771

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Williamson A Fed.

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

East Burton Flat *Morrow*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 16, T-20-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Samedan Oil Corporation

3. ADDRESS OF OPERATOR
10 Desta Drive Suite 240 East, Midland, Texas 79705

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

Unit Letter *L'* 1980 FSL & 660' FWL

Sec. 16 T-20-S, R-29-E

RECEIVED

MAR 23 '88

O. C. D.

14. PERMIT NO.
30-015-23995

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3273 GR 3288 KB

ARTESIA OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. MIRU Casing Pullers.
2. NUBOP.
3. Spot 20 sx "C" Neat in 4 1/2" Csg 6300'-6000' [TAG]
4. TOH w/2-3/8" tbg.
5. Locate free point on 4 1/2" Csg & shoot off (Estimated 4900').
6. TIH w/Tbg.
7. Spot 20 sx "C" neat 50' in and 50' out of Csg stub. [TAG]
8. Pull to 3250'.
9. Spot 30 sx "C" Neat in 8-5/8" 3250-3150'. [TAG]
10. Pull to 3030'.
11. Spot 20 sx "C" Neat in 8-5/8" Csg 3030-2950'.
12. TOH w/Tbg
13. Spot 20 sx "C" Neat in 8-5/8" Csg 80' - surface. 13 3/8" shoe.
14. Install Pipe Marker. P/A.

- Log Tops
- Atoka - 10,702'
 - Strawn - 10,420'
 - Wolfcamp - 9375'
 - Bone Springs - 5872'
 - Delaware - 3030'

SJS

18. I hereby certify that the foregoing is true and correct

SIGNED *Nick Hood*

TITLE Engineer

DATE 3/7/88

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE CHIEF

DATE 3.22.88