

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

C/SF

88210

17097

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR
David Fasken

3. ADDRESS OF OPERATOR
608 First National Bank Building, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
660' FNL & 1980' FWL

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Gulf Federal Com.

9. WELL NO.
1

10. FIELD AND POOL OR WILDCAT
Avalon (Morrow)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1, T-21-S, R-26-E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3192.5 GR.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

(Other) Intermediate Casing ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-1-82 to 2-6-82 drilled 12-1/4" hole from 395' to 2995' with fresh water.

2-6-82 set 8-5/8" K-55 32# & 24#/ft ST&C casing at 2995', c/w 900 sxs Halliburton Lite w/1/2# flocele/sx & 2% CaCl (s.w. 12.4 ppg, yield 1.91 cf/sx) plus 200 sxs Class "C" w/2% CaCl (s.w. 14.8 ppg, yield 1.32 cf/ft), plug down at 3:15 p.m. 2-6-82, circulated 108 sxs excess cement.

2-7-82 set 8-5/8" slips, N.U. B.O.P.'s & W.O.C. 29 hrs, tested choke manifold, wellhead valves, B.O.P.'s etc. w/ Yellow Jacket.

2-8-82 Drilling 7-7/8" hole with fresh water.

18. I hereby certify that the foregoing is true and correct

SIGNATURE Robert H. Angevine TITLE Robert H. Angevine Agent

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE 4-12-82

APR 26 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO