

## DEPARTMENT OF THE INTERIOR

## GEOLOGICAL SURVEY

c/SF

NM - 01119

6. IF IND ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Yates Federal "C"

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Burton Flat Mexico

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T20S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

## SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR

Exxon Corporation ✓

3. ADDRESS OF OPERATOR

P.O. Box 1600, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FWL &amp; 660' FNL of Section


AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 17 1/2" hole 3:00 p.m. 3-25-82.

Drilled 17 1/2" hole to 600'.

Ran 15 jts. 13 3/8" 54.5#, K-55 casing set at 584'.

Cement w/650 sx Dowell class "C" cement 2% CaCl, POB 5:30 p.m. 3-27-82.

Cement did not circulate. WOC.

Top of cement 410' - temp. survey.

Dump 1/2 yd. pea gravel in 13 3/8" annulus, run 1" tubing down 13 3/8" annulus, could not work past 180'. Pump 50 sx Dowell class "C" cement w/2% CaCl, WOC.

Run 1" tubing to 180' no fill, dump 1/4 yd. pea gravel and pump 25 sx class "C" w/2% CaCl. WOC.

Run 1" tubing to 179', 1' fill up, dump 1/4 yd. pea gravel. (see attachment)

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED S. J. Lowe TITLE Sr. Administrator DATE 4-29-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAY 5 1982

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side