

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Exxon Corporation

3. ADDRESS OF OPERATOR

P.O. Box 1600, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FEL and 1980' FSL of Sec

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

OCT 14 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

O. C. D.
ARTESIA, OFFICE

5. LEASE

NM - 01119

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yates Federal "C"

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Burton Flat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T20S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
Later

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8 3/4" hole to 11,901' T.D.

Ran 299 joints 5 1/2" casing, 20# L-80, 17# L-80, 17#, K-55, set at 11,901', w/stage tool at 4938', cement w/1480 sx lite, tailed w/200 sx Class "H", plug down 5:00 a.m. 9-26-82.

Open DV tool at 9:00 a.m. 9-27-82, cement w/100 sx Class "C".

Plug down 10:00 a.m. 9-27-82. TOC 3980 - temperature survey.

Tested 5 1/2" casing at 9:00 a.m. 10-1-82 w/1000# - held OK.

Preparing to perf.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

ACCEPTED FOR RECORD

TITLE Sr. Administrator

DATE 10-6-82

(ORIG. SGD.) DAVID R. GLASS

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

OCT 13 1982

TITLE

RECEIVED

OCT 13 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

OIL & GAS
MINERAL MANAGEMENT SERVICE
WASHINGTON, D.C.